



Color Variants

CM450110
stainless steel-backed glass frontage
Width 60 cm

CM450130
Aluminium-backed glass frontage
Width 60 cm

Included accessories

1 x measuring spoon.
1 x assembly screws.
1 x milk container.
1 x test strip.
1 x connection hose for milk frother.

CM450110
Fully automatic espresso machine 400 series
stainless steel-backed glass frontage
Width 60 cm
Controls at the top

Continuous flow heater means no waiting time and constant brewing temperature
Aroma brewing technology for a full aroma
Single portion cleaning
TFT touch display
One-touch operation
Personalisation function
Seven light settings

Type of beverage

Espresso / 2 x Espresso.
Coffee / 2 x Coffee.
White coffee.
Latte macchiato.
Cappuccino.
Milk froth.
Warm milk.
Hot water.

Handling

Rotary knob and TFT touch display operation.
Clear text display in 25 languages.
Personalisation function, up to 8 beverages can be personalised and memorised.
3 beverage size settings; can be individually adjusted to match the size of the cup.
5 coffee strength levels from mild to extra strong.
3 coffee and hot water temperature levels.
4 grinding level settings.
Height-adjustable coffee dispenser up to 15 cm.
Automatic slide-out function.

Features

Grinding unit with ceramic discs.
Separate container for second ground coffee type.
Water pump with 19 bar pressure.
Double grinding and brewing cycles for extra intensity for one beverage.
Double grinding and brewing cycles for two beverages.
Dispenser with integrated milk system.
Insulated milk container for up to 0.7 litres.
Integrated lighting with 3 LEDs.
Bean container for 1 kg.
Automatic adjustment of ground coffee quantity.
Removable 2.5 litre water tank.
Electronic fill level control for coffee beans and water.
Electronic water filter exchange indicator.
Electronic fill level control for drip tray and container for coffee dregs.

Safety

Child lock.
Safety shut-off.

Cleaning

Fully automatic rinse programme when machine is turned on/off.
Automatic quick rinsing of milk system.
Automatic cleaning and descaling programme.
Removable brewing unit.
Coffee dregs container and drip tray dishwasher-safe.
Milk frother dishwasher-safe.

Planning notes

Ideal installation height 95 cm (top edge of niche bottom), max. 120 cm.
The façade of the appliance extends 47 mm from the furniture cavity.

Characteristics
Built-in / Free-standing
Frothing nozzle
Yes
Display
Water protection system
no
Portion sizes
All cups
Dimensions of the product (mm)
455 x 590 x 562
Dimensions of the packed product (HxWxD) (mm)
540 x 620 x 670
Required niche size for installation (HxWxD)
450 x 564 x 514
Hot water spout
Yes
Adjustable programs
Standby function
No
Pump pressure (bar)
19
Simultaneous preparation of 2 cups
Yes
Included accessories
1 x measuring spoon, 1 x assembly screws, 1 x milk container, 1 x test strip, 1 x connection hose for milk frother
Optional accessories

Consumption and connection features

Electrical connection rating (W)
1700
Current (A)
10
Voltage (V)
220-240
Frequency (Hz)
50/60
Plug type
Gardy plug w/ earthing
Product group
Built-in coffee machine
Brand
Gaggenau
Product name/family
Product name / Commercial code
CM450110
Universal Product Code
825225910329
Main colour of product
Stainless steel
Typology
Fully automatic
Approval certificates
CE, ROSTEST, VDE
Length electrical supply cord (cm)
150.0
Length of electrical supply cord (in)
Recommened height for installation (in)
Recommened height for installation (mm)
450
Appliance Dimensions (h x w x d) (in)
Dimensions of the product (mm)
455 x 590 x 562
Dimensions of the packed product (in)
Dimensions of the pallet (in)
Dimensions of the packed product (HxWxD) (mm)
540 x 620 x 670
Net weight (lbs)
59
Net weight (kg)
26.76
Gross weight (lbs)
65
Gross weight (kg)
29.40
Capacity water container
2.5
2017-07-11
Page 1

When installing in a corner a side clearance of 200 mm is required.
Installation directly above 14 cm high WS in 59 cm standardised niche.
Special accessories (order as spare parts):
Part No. 467873 Water-filter cartridge
Part No. 311138 Descaling agent
Part No. 310575 Cleaning tablets

Connection

Total connected load 1.70 kW.
Connection cable 1.5 m with plug.

CM450110
Fully automatic espresso machine 400
series
stainless steel-backed glass frontage
Width 60 cm
Controls at the top
2017-07-11
Page 2

