- Steel mesh grilles included for speaker protection

Specifications

Speaker Design

2 - way

Woofer Size | in [mm]

6 3/4 [165]

Tweeter Size | in [mm]

1/2 [13]

DC Resistance | ohm

3.3

Peak Power (watts, per ANSI/CTA-2031-A)

300

Recommended Amplifier Power (watts RMS)

100

Sensitivity [SPLo] | dB @ 1W, 1m

90

Effective Frequency Range | Hz

40-20k

Mounting Hole Diameter | in [mm]

5 1/2 [140]

Top Mount Depth | in [mm]

3/16 [4]

Bottom Mount Depth | in [mm]

1 13/16 [47]

Tweeter Protrusion | in [mm]

0

Grilles

Yes

Tweeter Magnet Material

Neodymium

Tweeter Dome Materia

PEI [polyether imide

Tweeter Design

Balanced dome

Woofer Cone Material

Polypropylene

Woofer Surround Material

Polyester foam

Support



Manuals

2019 CS Coaxials | Multilingual | Download (/app/manuals/mids_tweets/cs/2019_CS_Coax.pdf)

Do you have a different model? Click Here (/product-manuals)



Support Links

Subwoofer / Speaker FAQ (/faq)



Contact Support

Technical Support
(405) 624-8583 (tel:+14056248583)
8am - 5pm CST
support@kicker.com (mailto:support@kicker.com)

Warranty Support
(405) 624-8510 (tel:+14056248510)
8am - 5pm CST
warranty@kicker.com (mailto:warranty@kicker.com)