



Color Variants

RF463707
Fully integrated, panel ready, with ice and water dispenser
Niche width 24" (61 cm)

Included accessories

1 x connection set.

Optional accessories

RA450022

Installation Accessories

RA422611
Stainless steel door panel with handle
RA423140
RA425110
Long stainless steel door handle
RA428811
Stainless steel door panel, handleless
RA460012
RA460020
Connecting element for vertically split appliance fronts (for a flush front)
RA464618
Ventilation grill, stainless steel

RF463707

Vario freezer 400 series

Fully integrated, panel ready, with ice and water dispenser

Niche width 24" (61 cm)

Left-hinged



Stainless steel interior with solid anthracite aluminium elements
Warm white and glare-free LED light spots

Opening assist for door with two options:

1. Push-to-open function for integration into handleless furniture front
 2. Pull-to-open function to facilitate opening the door using a handle
- The drawers in the RC and RF models are positioned at the same height.
With side-by-side installation, the glass shelves and door racks can be aligned on the same level

Flat stainless steel inner door, full-length
Integrated automatic ice maker with fixed water connection
Proximity sensor for ice and water dispenser
Illuminated dispenser for ice cubes, crushed ice and chilled water
TFT touch display
Net volume 11.2 cu.ft. (318 litres)
Energy Star certified

Operation

TFT touch display operation.
Clear text display in 44 languages.
Touch key operation for ice and water dispenser.

Technical Features

Dynamic cold air distribution with Multi-Flow Air System.
Automatic defrosting with defrost water evaporation.
Cushioned door closing system.
Sabbath mode certified by Star-K.
When rest mode is active, the appliance can only be opened using a handle.
Open-door and malfunction warning system.
Home network integration for digital services (Home Connect) wireless via WiFi.
The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Freezer compartment

No-frost technology with fast freezing at -22 °F.
Temperature adjustable from 3 °F to -11 °F.
4-star freezer compartment.
Freezing capacity 8.7 kg/24 h.
4 safety glass shelves, white glass, 2 of which are individually height adjustable.
2 fully extendable drawers with transparent front.

Ice and water dispenser

Warm white LED lighting.
Proximity sensor for automatic activation of light and touch keys for ice and water dispenser.
Integrated, with fixed inlet water connection.
Particle filter for water inlet, integrated in ventilation grille area.
Saturation indicator shown in TFT touch display.
Ice maker can be switched off independently.

Product Features

UPC code

825225961161

Variant color

Not applicable

Panel ready

Installation Type

N/A

Silence level

42

Watts

350

Fuse protection

10

Volts

110-120

Frequency

60

Total annual energy consumption

454.0

ENERGY STAR®

Yes

Approval certificates

CSA

Power Cord Length

118,1"

Plug type

120V-3 prong

Appliance dimensions (h x w x d) inch

83 3/4 " x 23 3/4 " x 24"

Required cutout size (HxWxD) (in)

84" x 24" x 24 3/4"

Appliance Width (in)

23 3/4 "

Height (in)

83 3/4 "

Depth (in)

24"

Product packaging dimensions

(HxWxD)

84.25 x 27.36 x 29.92

Total unit gross capacity - AHAM

11.2

Net weight

334.000

Gross weight

367.000

Consumption and connection features

2021-10-26

Page 1

Ice cube production approx. 2.9 lb (1.1 kg)/24 h.

Ice cubes and crushed ice.

Removable ice storage container with approx. 6.6 lbs. (3.2 kg) capacity.

Chilled water supply approx. 1.3 litres.

Consumption data

Energy consumption 453.98 kWh/year.

Noise level 42 dB (re 1 pW).

Planning notes

Flat hinge.

Door opening angle of 115°, fixable at 90°.

Max. door panel weight 147 lbs. (67kg).

Shut-off valve for water connection must be planned next to the appliance and always be accessible.

If the water pressure exceeds 116 psi, connect pressure relief valve between water tap and hose set.

Rating

Total rating 1.079 kWh/24 h.

Total Amps: 10 A.

Connecting cable 118" (3.0 m), detachable.

Cold water connection required.

Electrical location 6" above ground in lower left corner of unit.

Supply hose 47,2 INCH (1.2 m) with 1/4" male compression fitting (standard icemaker connector).

Water pressure 29 to 116 psi.

GAGGENAU

