

EMB10DFM70 LANDSCAPE SERIES

(2) 10" ACTIVE/PASSIVE DOWN-FIRING SUBWOOFER



Size	13 h x 12 w x 12 d (in) 330 h x 305 w x 305 d (mm)
Freq Response	20-150Hz \pm 3dB
Impedance	70 volt
Sensitivity	90dB 2.83V /1m
Power req.	70V (100W Transformer)
Woofer	(2) 10" (254mm) Active/Passive
Enclosure	Aluminum
Finish	Satin Black
Weight	49lbs/22kg

(1) 10" Internal Active Woofer (1) 10" EMB Passive Radiator

One of many available options in the EMB II Subwoofer series features a very contemporary down-firing cabinet design and a size that isn't obtrusive. Built from solid aluminum and powder coated to a fine finish, the exquisite craftsmanship of this powerful subwoofer exudes luxury and performance. The EMB10DFM is built tough to withstand extreme weather, protecting components with sealed aircraft aluminum enclosures, powder coating, aluminum constructed domes, rubber surrounds and marine grade hardware.

Internally the EMB10DFM utilizes our famous "Energy Multiplying Bandpass" technology to obtain high output and low distortion from a very compact enclosure. Inside the cabinet features a specially designed 10" woofer and pneumatically phase coupled passive radiator, with aluminum cones and rubber surrounds. The EMB10DFM subwoofer has been tuned to perform beyond 35Hz, (which is predominantly where most recorded bass frequencies tend to occur) all the way down to 20Hz!

The 70 volt version of this speaker comes with a 100 watt, all copper, toroidal transformer for low distortion and frequency loss. We recommend pairing this passive sub with our M1000 class D amplifier which provides 1000W of clean power at 70V and features a full DSP digital processor. You can power up to 8 of these powerful subwoofers in 70V mode with a single M1000.

James
LOUDSPEAKER™

535 Airpark Road, Napa, CA 94558
Ph: 707.265.6343
www.jamesloudspeaker.com

EARTH SHAKING PERFORMANCE

20150811