

## 8" In-Ceiling Speaker



# R-1800-C

Perfect for those who want excellent performance, reliability and durability at an affordable price, the R-1800-C brings dynamic acoustic performance to both home and commercial environments.

The R-1800-C employs an 8-inch polymer-cone woofer and a large motor structure for high sensitivity. A coaxially mounted 1-inch polymer-dome tweeter distributes smooth, clear highs over a wide area.

The speaker's mounting system makes installation a breeze, while its paintable aluminum grille provides added rust protection in moisture-prone areas such as bathrooms, kitchens and saunas.

While the R-1800-C will fit into our latest IK-800-C installation kit, it can also be used in conjunction with the ME-800-C fire-rated enclosure.

- Good sensitivity and power handling
- Paintable to match ceiling
- Packaged individually

### SPECIFICATIONS

frequency response	56Hz-20kHz +/- 3dB
power handling	40 watts (160 watts peak)
sensitivity	89dB @ 2.83V/1 meter
nominal impedance	8 ohms compatible
drive components	Two-way system using one 1" (2.5cm) polymer dome, tweeter and one 8" (20.3cm) poly woofer
dimensions	11" (27.9cm)
cutout dimensions	9.8" (24.9cm)
installation kit	IK-800-C (sold separately)
weight	5.8 lbs (2.6 kg)
accessories	ME-800-C fire-rated enclosure (sold separately)
built from	2006

www.klipsch.com  
1-800-KLIPSCH

All specifications are subject to change without notice. ©2007

