

SPECIFICATIONS

POWER OUTPUT 8 ohms AUSGANGSLEISTUNG (8 Ohm)	2x220W
POWER OUTPUT 4 ohms AUSGANGSLEISTUNG (4 Ohm)	2x400W
FREQUENCY RESPONSE (-3dB) ÜBERTRAGUNGSBEREICH	10Hz-70kHz
TONE CONTROL KLANGREGELUNG	+/- 10 dB
DISTORSION VERZERRUNG	< 0,025%
S/N RATIO SIGNAL RAUSCHABSTAND	> 102 dB
CHANNEL SEPARATION KANALTRENNUNG	> 75 dB
INPUT IMPEDANCE EINGANGSIMPEDANZ	47KΩ Unbal. / bal. 47KΩ
DAC DIGITAL AUDIO CONVERTER 24bit-192kHz	BurrBrown PCM1796
USB B DAC Adaptive for playback / asynchronous for record	XMOS USB3318 / 24bits 192kHz
IN LEVEL (CD/AUX...) EINGANGSPEGEL (CD/AUX/...)	< 500mV
INPUT LEVEL PHONO MM EINGANGSPEGEL PHONO MM	7mV
AC INPUT NETZSPANNUNG	115-230V
POWER CONSUMPTION MAX LEISTUNGS-AUFNAHME MAX.	<700W (StandBy < 0,5W)
TRANSFORMER(S) TRANSFORMATOR(EN)	1 (700VA)
DIMENSIONS ABMESSUNGEN H x B x T	H.210 x l.430 x D.476
NET WEIGHT / GROSS WEIGHT GEWICHT	21,4 kg