SUMMIT

SBC635MBINKIF



33.5" x 24" x 25.88" (H x W x D)

Built-in beer dispenser, auto defrost w/digital thermostat and panel-ready door; sold without tap kit for do-ityourselfers to install their own taps

Highlights:

Allows you to install your own custom tap equipment

Customizable door front accepts full overlay panels for a seamless look that can blend into cabinetry

Designed for built-in installation under the counter

Product Features:

| Full-sized beer dispenser | Large 5.6 cu.ft. interior can accept a full half barrel keg, two 1/6 barrel kegs, or a pony keg | |
|--|---|--|
| Built-in capable | Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require extra space due to the door design. Width should be 25" to 25 1/4". For more information, see the user manual | |
| NO TAP KIT | Install your own tapping equipment for a customized beer cooler | |
| Panel-ready door | Integrated stainless steel door frame accepts full overlay panels, allowing you to customize the door or blend it into your cabinetry design (panel dimensions: 23 3/4" W x 30 13/16" H and at least 3/4" thick; maximum weight: 10 lbs.) | |
| Digital thermostat | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit | |
| Ideal beer temperature | Operates between 33° and 50°F to keep a variety of beers stored at just the right serving temperature | |
| Automatic defrost | Reduced maintenance with auto defrost system | |
| Fully finished black cabinet | Allows the unit to be used freestanding | |
| Casters included (ship unassembled) SUMMIT APPLIANCE DIVISION. FELIX STO | To make the beer dispenser portable, install this set of 2 1/2" high locking casters | |



SBC635MBINKIF Specifications:

| Overview | | |
|--|--|--|
| Height of Cabinet | 33.5" (85 cm) | |
| Width | 24.0" (61 cm) | |
| Width with Door Open | 25.25" (64 cm) | |
| Depth | 25.88" (66 cm) | |
| Depth with door at 90° | 47.5" (121 cm) | |
| Capacity | 5.6 cu.ft. (159 L) | |
| Defrost Type | Automatic | |
| Door | Panel-Ready | |
| Cabinet | Black | |
| US Electrical Safety | ETL | |
| Canadian Electrical Safety | ETL-C | |
| Energy Usage/Year | 310.0kWh/year | |
| Amps | 0.86 | |
| Voltage/Frequency | 115 V AC/60 Hz | |
| Weight | 100.0 lbs. (45 kg) | |
| Shipping Weight | 105.0 lbs. (48 kg) | |
| Parts & Labor Warranty | 1 Year | |
| Compressor Warranty | 5 Years | |
| Beer Dispenser | | |
| Door Swing | RHD | |
| Reversible | Factory Reversible | |
| Thermostat Type | Digital | |
| Fan Type | Exterior | |
| Refrigerant | R600a | |
| | | |
| Refrigerant Amount | 1.13 oz. | |
| Refrigerant Amount High Side PSI | 1.13 oz. 250.0 | |
| | | |
| High Side PSI | 250.0 | |
| High Side PSI Low Side PSI | 250.0 110.0 | |
| High Side PSI Low Side PSI Inter Height | 250.0 110.0 28.0" (71 cm) | |
| High Side PSI Low Side PSI Inter Height Interior Width | 250.0 110.0 28.0" (71 cm) 20.5" (52 cm) | |
| High Side PSI Low Side PSI Inter Height Interior Width Interior Depth | 250.0 110.0 28.0" (71 cm) 20.5" (52 cm) 19.0" (48 cm) | |
| High Side PSI Low Side PSI Inter Height Interior Width Interior Depth Compressor Step Height | 250.0 110.0 28.0" (71 cm) 20.5" (52 cm) 19.0" (48 cm) 8.25" (21 cm) | |

