AT-VM95C Cartridge & Stylus

Frequency Response	20-20,000 Hz
Channel Separation	18 (dB at 1 kHz)
Vertical Tracking Angle	23°
Vertical Tracking Force	1.8-2.2 g (2.0 g standard)
Stylus Construction	Bonded round shank
Recommended Load Impedance	47,000 ohms
Coil Impedance	3.3 k ohms (1 kHz)
DC Resistance	485 ohms
Coil Inductance	550 mH (1 kHz)
Output Voltage	4.0 mV (1 kHz, 5 cm/sec.)
Output Channel Balance	2.5 dB (1 kHz)
Stylus Shape	0.6 mil conical
Cantilever	Aluminum pipe
Static Compliance	17 x 10 – 6 cm / dyne
Dynamic Compliance	6.5 x 10 – 6 cm / dyne (100 Hz)
Mounting	Half-inch
Cartridge Weight	6.1g
Dimensions	17.2 mm (0.68") H × 18.9 mm (0.74") W × 28.3 mm (1.20") D
Accessories Included	Two 11 mm installation screws, two 8 mm installation screws, two washers
Model	AT-VM95C
Mounting Feature	Half-inch mount
Recommended Load Capacitance	100 to 200 pF
Replacement Stylus	AT-VMN95C
Stylus Size	0.6 mil
Type	VM Stereo Dual Magnet
Weight	6.1 g (0.22 oz)
Wire Used for Coil	T.P. Copper