

5 SERIES 42" AND 54"W. OUTDOOR GAS GRILLS

COMMERCIAL-TYPE COOKING POWER AND FEATURES

- Extremely large grilling surfaces
 - ■42" wide grill 706 sq. in. 4.9 sq. ft.
 - ■54" wide grill 950 sq. in. 6.6 sq. ft.
- Polished/brushed edge canopy design
- Stainless steel grates are an excellent conductor of heat to cook food evenly
- Ceramic heat distribution system provides even heat distribution
 - •White briquettes with "flip-clean" self-clean design
- 25,000 BTU 304 stainless steel U-shaped burner provides superior corrosion resistance
- EasyLift™ Canopy Assist System is built into canopy and hidden from view
- Control panel illumination with dedicated Viking Blue LED lighting above every control knob
- Laser-etched graphics on control panels
- Smoker box may be removed for use of entire grilling surface
- Rotisserie system
 - ■Gourmet-Glo™ 15,000 BTU one-piece infrared rotisserie burner
 - Fully enclosed 1/2" stainless steel rotisserie rod with stainless steel forks
 - Heavy-duty rotisserie motor
- Push-to-turn 120V electric ignition system provides a positive, consistent, and continuous spark for easy ignition
- **EXCLUSIVE** automatic re-ignition system
- Halogen lighting mounted on the inside of canopy provides ample lighting for nighttime grilling
- Stainless steel warming rack can be adjusted to two different positions
- Hermetically sealed, numerical thermometer gives approximate temperatures for grilling, smoking, and warming

EASY MAINTENANCE AND CLEANUP

Full-width, pull-out drip tray

- Individual grease management trays under each burner area
- Stainless steel ball-bearing roller glides allow drip tray to pull out easily and remain level when fully extended

Viking Professional 5 Series – VGBQ/VGIQ



TRUSEAR™ INFRARED BURNER (OPTIONAL)

- EXCLUSIVE 30,000 BTU
- Creates an intense, searing heat (1,200+ degrees F), which caramelizes the outside of food items locking in natural juices and flavors
- Available on 42" and 54" VGIQ models

MODEL NUMBERS

- ■VGBQ54224 42"W. Outdoor Gas Grill
- ■VGBQ55424 54"W. Outdoor Gas Grill
- ■VGIQ542241 42"W. Outdoor Gas Grill with TruSear™ Infrared Burner
- ■VGIQ554241 54"W. Outdoor GasGrill with TruSear™ Infrared Burner
- ■VGBQ models also available in 30" and 36"W. models
- When installing grill in combustible-type material, an insulated jacket (INJK) is required (purchased separately)

ACCESSORIES

- BQC5421SS 42" Grill Cart
- BQC5541SS 54" Grill Cart
- ■INJK42 Insulated Jacket for 42" Grill
- ■INJK54 Insulated Jacket for 54" Grill
- ■WG542 Wind Guard for 42" Grill
- WG554 Wind Guard for 54" Grill
- ■WR542 Warming Rack for 42" Grill
- ■WR554 Warming Rack for 54" Grill
- Vinyl Covers
- RFK Rotisserie Forks

COLOR FINISHES

Available in Stainless Steel (SS)

WARRANTY

- 2-year full complete product
- 90-day full cosmetic parts such as glass, painted items and decorative items





5 SERIES 42" AND 54"W. OUTDOOR GAS GRILLS

Viking Professional 5 Series – VGBQ/VGIQ

	GAS 42" AND 5	4" W. ULTRA-PREMIUI	M 5 SERIES GRILLS		
DESCRIPTION	VGBQ54224/VGIQ54224		VGBQ55424/VGIQ55424		
Overall Width	42" (106.7 cm)		54" (137.2 cm)		
Overal Depth	29" (73.6 cm)				
Cutout Width	41-1/4" (104.8 cm)		53-1/4" (/4" (135.3 cm)	
Cutout Depth	24-3/8" (67.9 cm)				
Cutout Height	10-1/8" (25.7 cm)				
Gas Requirements	Natural: standard residential 1/2" (1.3 cm) ID gas service line. LP/Propane: Equipped with high-capacity hose/regulator assembly for connection to standard 5 gal., 20 lb. LP/Propane gas cylinder with a Type 1, QCC-1 connector or standard residential 1/2" (1.3 cm) ID gas service line.				
Electrical Requirements	120VAC/60Hz – Power supply cord with 3-prong grounded plug attached to gri ∥ 120VAC/60Hz – 3′ (91.4 cm) power supply cord with 2-prong grounded plug attached to rotisserie motor				
Maximum Amp Usage	2.2 amps		3.0 amps		
Grill Burner Rating	25,000 BTU NAT./22,500 BTU LP (7.3 kW NAT./6.5 kW LP)				
Rotisserie Burner Rating	15,000 BTU NAT./13,500 BTU LP (4.4 kW NAT./4.0 kW LP)				
TruSear™ Burner Rating	-	25,000 NAT./22,500 LP	-	25,000 NAT./22,500 LP	
Approximate Shipping Weight	255 lb (116 kg)		330 l bs (149.7 kg)		

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.



VIKING RANGE, LLC 111 FRONT STREET GREENWOOD, MISSISSIPPI 38930 USA

For detailed product information, model numbers, or to request a quote call 1-888-845-4641 or visit vikingrange.com © 2014 Viking Range, LLC All rights reserved. Specifications subject to change without notice.