## PSB9240DF GE Profile™ Series Advantium® 240V - 30 in. Wall Oven

# Advantium wall oven/GE Profile<sup>™</sup> Series cooking tower dimensions and cabinet installation information (in inches)

Note: Cabinets installed adjacent to wall ovens must have an adhesion spec of at least a 194°F temperature rating.

Note: 2" minimum between cutouts when installed above warming drawer or single wall oven.

### Installation

Before installing, consult installation instructions packed with product for current dimensional data.



**Note:** Advantium wallovens can be installed below GE/GE Profile Series nondowndraft gas and electric cooktops. It CANNOT be installed below induction or Monogram (2GU3841385) gas cooktops.

**Note:** Advantium wall oven comes with two lower trim pieces. One is for use above 36-inch height installations and one is for use below 36-inch installations. Use of the accessory drawer will replace the bottom trim piece for applicable installations. Please see installation instructions for full details.



) imagination at work

For answers to your Monogram® or GE® appliance questions, visit our website at geappliances.com or call GE Answer Center® service, 800.626.2000.





Listed by

Underwriters

aboratories

### PSB9240DF GE Profile™ Series Advantium® 240V - 30 in. Wall Oven

### Preparation WITH an Accessory Drawer

#### Prepare the opening

The Advantium 240V can be installed in combination with other GE/Monogram appliances. Always follow each product's Installation Instructions to compete the installation.

#### Single Oven Installation:

Order a 30" wide single oven cabinet or cut the opening in a wall to the dimensions shown.

- \* For existing cutouts, a maximum width of 28-1/2" is acceptable. If the opening is slightly wider, secure a furring strip on each side of the cutout for securing the oven.
- Always maintain 36-3/4" minimum height from the floor to the cutout in any single or combined installation.
- Allow 3/4" to 2-1/8" case trim overlap on the sides and 7/8" overlap on the bottom of the opening for



all models. The amount of overlap on the sides depends on the actual cutout width. Allow 1-1/4" case trim overlap on the top for models PSB9240 and for models ZSC2200, ZSC2201 and ZSC2202.

• Oven overlaps will conceal cut edges on all sides of the opening.



#### Prepare the opening (cont.)

When installed over a single oven or a warming drawer, allow at least 2" between the two openings. This separation will provide clearance for bottom overlap of the Advantium 240V and the other appliance overlaps.

Construct a solid oven floor of 3/8" min. thick plywood supported by  $2 \times 4$  or  $2 \times 2$  runners on all sides.

• the support must be level and rigidly mounted, flush with the bottom edge of the cutout.



\* For existing cutouts, a maximum width of 28-1/2" is acceptable. If the opening is slightly wider, secure a furring strip on each side of the cutout for securing the oven.
Note: Additional clearances between the cutouts may be required. Check to be sure the oven supports above the Warming Drawer location do not obstruct the required interior depth and height. See Warming Drawer installation instructions for details.

# Installation over a GE/Monogram Oven and Warming Drawer:



\* For existing cutouts, a maximum width of 28-1/2" is acceptable. If the opening is slightly wider, secure a furring strip on each side of the cutout for securing the oven. Note: Additional clearances between the cutouts may be required. Check to be sure the oven supports above the Warming Drawer location do not obstruct the required interior depth and height. See Warming Drawer installation instructions for details. **CAUTION:** For personal safety, the mounting surface must be capable of supporting the cabinet load, in addition to the added weight of this approximate 80-pound oven and 30pound drawer, plus additional oven loads of up to 50 pounds or a total weight of 160 pounds.

# PSB9240DF GE Profile™ Series Advantium® 240V - 30 in. Wall Oven

### **Features and Benefits**

- Speedcook Technology (240) Enjoy oven-quality results two to eight times faster than a conventional oven
- 4 Ovens-In-1 Expand your cooking versatility with four ovens in one
- Halogen Heat Skip the preheating with nearly instantaneous halogen heat
- Over 175 Preprogrammed Recipes Preprogrammed recipes make meals easy
- Custom Recipe Saver Conveniently store cooking instructions for up to 30 different recipes
- Allows for use with JX2200/2201 storage drawer
- Under-the-counter installation flexibility
- Model PSB9240DFWW White on white
- Model PSB9240DFBB Black on black



