Specifications

Turntable

Motor	DC servo
Drive Method	Direct drive
Speeds	33-1/3 RPM, 45 RPM, 78 RPM
Turntable Platter	Die-cast aluminum, rubber damper
Starting Torque	1.0 Kgf.cm
Braking System	Electronic brake
Wow and Flutter	< 0.1% (WTD) at 3 kHz (JIS)
Signal-to-Noise Ratio	> 60 dB
Cartridge Type	VM (AT-VM95EBK)
Output Level	PHONO: 4.0 mV nominal at 1 kHz, 5cm/sec
Power Supply Requirements	100 to 240 V, 50/60 Hz
Power Consumption	8 W
Dimensions	450 mm (18") × 352 mm (14") × 161 mm (6.3") (W×D×H)
Weight	Approx. 10.4 kg (23 lbs)
Accessories Included	・Dust cover ・Rubber mat ・Platter ・Dust cover hinges ・Counterweight ・Subcounterweight ・Headshell (AT-LT10) with VM stereo cartridge (AT-VM95E BK) ・45 RPM adapter ・RCA audio cable (Approx. 1.0 m (3.3')) ・Power cable (Approx. 1.8 m (5.9'))
Tonearm Type	Static balanced J-shaped tonearm
Effective Arm Length	247 mm (9.7")
Overhang	15 mm (0.59")
Tracking Error Angle	Less than 2.0°
Stylus Pressure Adjustment Range	0.0 to 4.0 g
Applicable Cartridge Weight	14.0 to 20.0 g (including headshell) (When using subcounterweight: 17.5 to 23.5 g)
Replacement Stylus	AT-VMN95EBK
Replacement Headshell	AT-LT10
Notes	For product improvement, the product is subject to modification without notice.