

# HCB 2092G

Fully Integrated Appliances

# LIEBHERR

## Refrigeration and Freezing



home.liebherr.com

### HCB 2092G

Energy consumption (kWh / y)	580
Estimated Yearly Energy Cost* in US \$	81
Sound rating** dB(A)	39
Total refrigerator capacity cu.ft. (l)	12.9(365)
BioFresh compartment cu.ft. (l)	2.4(6.9)
Freezer capacity cu.ft. (l)	6.0(170)
Electronic control	MagicEye with digital temp. display, touch electronic
Defrost type	Automatic
Interior light	LED Light column both sides
Number of shelves	4
Number of door racks	6
Number of BioFresh drawers	2
Number of freezer drawers	2
Refrigerator Temperature range °F (°C)	+37°F to +45°F (+3°C to +7°C)
Freezer Temperature range °F (°C)	+7°F to -17°F (-14°C to -27°C)
Water filter	yes
Ice maker	Fixed water connection
Ice cube output lbs. (kg.)	3.1 (1.4)
Ice cube stock lbs. (kg.)	6(2.7)
Door hinges	left/right
<b>Product dimensions</b>	
in inch (H / W / D)	79 13/16" / 35 7/8" / 24 1/16"
in cm (H / W / D)	202.7/91.6/61.5
<b>Cut out dimensions</b>	
in inch (H / W / D)	80"-81 5/8" / 36 1/16" / 25"
in cm (H / W / D)	203.2-207.2/91.5/63.5
Net weight lbs. (kg)	359.3(163)
Voltage V / Hz	115/60

\* Energy Cost will depend on utility rates and use. Estimated energy cost based on a national average electricity cost of 14 cents per KWh.

\*\* Noise output – according to EN 60704-3



### Accessories

<b>Water Filter</b>	9880980/7440002/ 9883057
<b>Stainless Steel Round Handles</b>	9900339
<b>Brushed Aluminium Square Handles</b>	9900513
<b>Stainless Steel Panels Refrigerator 80"</b>	9900337
<b>Stainless Steel Panels Refrigerator 84"</b>	9904386
<b>Stainless Steel Panels Freezer Drawers</b>	9900323

### Features

#### Bio Fresh

Preserve just-bought groceries for optimum food freshness, while sealing in flavors and maintaining essential vitamins and minerals.

#### Duo Cooling

Lengthen the shelf life and preserve the flavor of your foods with a dual refrigeration system that creates ideal conditions in both the refrigerator and freezer.

#### Ice Maker

Liebherr's automatic IceMaker produces perfect ice cubes and keeps a constant supply on hand for every occasion.

#### Soft System

Ensure the door closes gently to reduce any unnecessary sounds.

#### Telescopic Rails

Store food securely within reach thanks to fully extendable pull-out drawers. The SoftTelescopic system provides convenient and reliable self-retraction with soft closing.

# Diagrams

### Product Dimensions

78-3/4" 2000 mm

34" 864 mm

22-1/16" 561 mm

42-3/8" 1076 mm

90° 105°

1/4"

35-13/16" 910 mm

4" 102 mm

Allow door swing clearance at locations next to a wall.

The refrigerator door must open to a minimum of 90° to allow the crispers to open and the shelves to be removed.

Center rail 1-7/8" 48 mm

Door 1-7/16" 37 mm

Hinge 1-11/16" 43 mm

1-7/8" 48 mm

3-3/4" 95 mm

13-1/2" 343 mm

Height can be increased by 1-1/2" (40 mm) by turning the levelling feet at the front and the height adjustable roller units at the appliance rear.

### Panel Dimensions

#### Inset Installation Style

17 - 3/4" (451.5 mm)

17 - 3/4" (451.5 mm)

13 - 7/16" (341 mm)

35 - 3/4" (909 mm)

4" (102 mm)

#### Frameless Installation Style

17 - 7/8" (454.5 mm)

17 - 7/8" (454.5 mm)

13 - 7/16" (341 mm)

36" (915 mm)

4" (102 mm)

The height of this panel cannot be reduced for higher toe kicks as it will reveal structural elements of the appliance. Instead, install appliance on a platform and adjust the opening height to accommodate.

Cabinet opening A	Refrigerator door panel B
80"	45-1/2" (1156 mm)
84"	49-1/4" (1251 mm)

Cabinet opening A	Refrigerator door panel B
80"	45-5/8" (11659 mm)
84"	49-3/4" (1264 mm)

Minimum panel thickness is 5/8" (16 mm).

Maximum panel thickness is 3/4" (20 mm).

Maximum weight of the refrigerator panel is 26.5 lbs (12 kg).

**IMPORTANT**  
Risk of interference with the adjacent panels!  
Do not use wider panels as given in the illustration above!

### Cutout Dimensions

80" or 84"

2-3/4" (70 mm)

7-5/8" (195 mm)

Water line outlet

Water supply line

36" Single

72" Side by Side

Inset cabinet Depth D

24" + panel thickness

Frameless cabinet Depth D

24"

### Ventilation Requirements

The appliance do not require ventilation considerations in the cabinetry. The required airflow is directed through the toe kick base. It is important to use the provided cover grille for the ventilation opening. This opening must not be covered.

Subject to modification. For up-to-date information, visit [home.liebherr.com](http://home.liebherr.com).  
Specifications are for planning purposes only. For more detailed information, refer to installation instructions or Design Guide.