

VT65



33.5" x 23.63" x 23.5" (H x W x D)

Built-in undercounter laboratory freezer capable of -30° C (-22° F) operation

Highlights:

Commercially listed to NSF-7 standards and meets UL-471

Precise temperature control with a digital thermostat

Factory installed lock provides security you can count on

Product Features:

Built-in capable	Front-breathing system allows the unit to be used built-in
Commercially approved	UL-S listed to NSF-7 commercial standards and meets UL commercial standard 471
Slim counter height dimensions	24" footprint fits easily in space-challenged facilities
-30° C (-22° F) capable	Low temperature operation ideal for vaccines, pharmaceuticals, and long-term preservation of frozen food
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened
Factory installed lock	Keyed lock offers convenient security
Digital thermostat	Electronic controls for precise temperature management
Alarm with temperature display	Provides external temperature readout and includes programmable alarm to warn of temperature variations
Manual defrost	No temperature fluctuations with an energy efficient manual defrost system

VT65 Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	UL-S
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Shipping Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	2.76 oz.
Interior Drawers	Yes
Drawers Qty	3
Temperature Range	-20°C to -30°C

