

# UM12N



Colour range  
Body



Blue  
grey – BG



Antique  
white – AW



White – WH



Blue – MB



Stainless  
steel – SS



Graphite  
matt – MG



Glossy  
black – BK



Burgundy  
red – BU



Emerald  
green – EG



Optional RAL – RA

Finishes  
Knobs, handles, frames



Brass – G



Copper – P



Chrome – C



Burnished – B

Optional solid door version


optional +

Order code: add letter “Q” before the “N” letter

Available ovens

|                          |                          |
|--------------------------|--------------------------|
| Electric oven            |                          |
| Primary oven:            | Secondary oven:          |
| UOV 80 E3 TFT S          | UOV 30 E3 TFT            |
| Maximum input:<br>3.7 kW | Maximum input:<br>2.5 kW |

Configurations



Electric oven

UM12FDNS3  
Brass/Copper/Chrome/Burnished

Fuel requirements

Natural gas / Liquid propane  
Voltage: 240 Volts  
Amps: 25.8

*\*Insufficient amperage may lower heating performance when multiple functions are being used at the same time*


Consumption



Double ring  
Dual burner  
20000 btu/h /  
900 btu/h



Double ring  
burner  
16500 btu/h /  
6200 btu/h



Griddle  
10500 btu/h /  
2000 btu/h +  
7000 btu/h /  
1400 btu/h



Big burner  
10500 btu/h /  
2000 btu/h



Small burner  
7000 btu/h /  
1400 btu/h

Complements & accessories

|      |        |                    |         |
|------|--------|--------------------|---------|
| Hood | UAM120 | Ladle holder panel | AM4-120 |
|------|--------|--------------------|---------|

Technical drawing & dimensions

