

## SBC635M7CMTWIN



33.5" x 23.63" x 25.5" (H x W x D)

Commercially listed dual tap coffee dispenser in black, with a combination nitro/flat coffee tap kit in stainless steel

## **Highlights:**

Commercially listed to NSF-7 standards

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro-infused cold brew drafts

Digital thermostat lets you set the perfect temperature for any cold brew

## **Product Features:**

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments, with an NSF-listed tap kit	
Dispenses both flat and nitro-infused coffee	Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro-infused drafts from two cornelius kegs	
Complete tap kit	Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs	
Automatic defrost	Reduced user maintenance with auto defrost operation	
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit	
Ideal temperature	Operates between 33° and 50°F to keep your coffee stored at just the right serving temperature	
Fully finished black cabinet	Allows the dispenser to be used freestanding	
Reversible door	User-reversible door swing for added flexibility	
Casters included (ships unassembled)	To make the unit portable, install this set of 2 1/2" high locking casters	





## **SBC635M7CMTWIN Specifications:**

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Width with Door Open	25.0" (64 cm)
Depth	25.5" (65 cm)
Depth with door at 90°	47.0" (119 cm)
Capacity	5.6 cu.ft. (159 L)
Defrost Type	Automatic
Door	Black
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Energy Usage/Year	310.0kWh/year
Amps	0.86
Voltage/Frequency	115 V AC/60 Hz
Weight	80.0 lbs. (36 kg)
Shipping Weight	83.0 lbs. (38 kg)
Estimated Time to Ship	3 to 5 days
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Kegerator	
Door Swing	RHD
Reversible	
Reversible	Yes
Tap Kit	Yes Yes
Tap Kit	Yes
Tap Kit Height with Tap	Yes 49.0" (124 cm)
Tap Kit  Height with Tap  Number of Taps	Yes 49.0" (124 cm) 2
Tap Kit  Height with Tap  Number of Taps  Thermostat Type	Yes 49.0" (124 cm) 2 Digital
Tap Kit  Height with Tap  Number of Taps  Thermostat Type  Refrigerant	Yes 49.0" (124 cm) 2 Digital R600a
Tap Kit  Height with Tap  Number of Taps  Thermostat Type  Refrigerant  Refrigerant Amount	Yes 49.0" (124 cm) 2 Digital R600a 1.13 oz.
Tap Kit  Height with Tap  Number of Taps  Thermostat Type  Refrigerant  Refrigerant Amount  High Side PSI	Yes 49.0" (124 cm) 2 Digital R600a 1.13 oz. 250.0
Tap Kit  Height with Tap  Number of Taps  Thermostat Type  Refrigerant  Refrigerant Amount  High Side PSI  Low Side PSI	Yes 49.0" (124 cm) 2 Digital R600a 1.13 oz. 250.0 110.0
Tap Kit  Height with Tap  Number of Taps  Thermostat Type  Refrigerant  Refrigerant Amount  High Side PSI  Low Side PSI  Inter Height	Yes 49.0" (124 cm) 2 Digital R600a 1.13 oz. 250.0 110.0 28.0" (71 cm)
Tap Kit  Height with Tap  Number of Taps  Thermostat Type  Refrigerant  Refrigerant Amount  High Side PSI  Low Side PSI  Inter Height  Interior Width	Yes 49.0" (124 cm) 2 Digital R600a 1.13 oz. 250.0 110.0 28.0" (71 cm) 20.5" (52 cm)
Tap Kit  Height with Tap  Number of Taps  Thermostat Type  Refrigerant  Refrigerant Amount  High Side PSI  Low Side PSI  Inter Height  Interior Width  Interior Depth	Yes 49.0" (124 cm) 2 Digital R600a 1.13 oz. 250.0 110.0 28.0" (71 cm) 20.5" (52 cm) 19.0" (48 cm)



