

# UP36N



## Colour range

### Body



Blue grey - BG



Antique white - AW



White - WH



Blue - MB



Stainless steel - SS



Graphite matt - MG



Glossy black - BK



Burgundy red - BU



Emerald green - EG



Optional RAL - RA

## Finishes

### Knobs, handles, frames (optional)



Brass - G



Copper - P



Chrome - C



Burnished - B

## Optional solid door version

optional +

Order code: add letter "Q" before the "N" letter

## Noblesse frames

optional → p. 138


Available ovens

Electric oven


Primary oven:  
UOV 80 M  
Maximum input:  
3,7 kW

Configurations

6 burners with fry top\*



Induction



Electric oven

UP36FNMP

Brass/Copper/Chrome/Burnished

UPI366NMP

Brass/Copper/Chrome/Burnished


Fuel requirements


Natural gas / Liquid propane  
Voltage: 240 Volts  
Amps: 15.4


All electric  
Voltage: 240 Volts  
Amps: 63.3


*\*Insufficient amperage may lower heating performance when multiple functions are being used at the same time*


Consumption


 Bridge induction zone  
Ø 7" 1/4 + Ø 7" 1/4  
1,85 kW + 1,85 kW


 Induction zone  
Ø 5" 3/4  
1,4 kW


 Induction zone  
Ø 7" 1/4  
1,85 kW

 Induction zone  
Ø 8" 11/16  
2,3 kW

 Double ring Dual burner  
25000 btu/h /  
900 btu/h

 Griddle  
10500 btu/h /  
2100 btu/h +  
6100 btu/h /  
1350 btu/h

 Big burner  
10500 btu/h /  
2050 btu/h

 Small burner  
6100 btu/h /  
1350 btu/h

Complements & accessories

Hood

UAG36

Hood

UANB36

Ladle holder panel

AM4-90

Brass/Copper/Chrome/Burnished

Technical drawing & dimensions

