Specifications

Audio Specifications

XLR input Impedance	40kΩ
RCA input Impedance	20kΩ
Input Sensitivity	1.48Vrms@Stereo/Mono mode, 1Vrms@Bridge mode
Output Power in Stereo/Mono mode	2x 250WRMS@8Ω, 2x 450WRMS@4Ω
Output Power in Bridged mode	1x 500WRMS@8Ω, 1x 900WRMS@4Ω (Music signal only)
Frequency Response	20-20kHz (+0, -0.15dB), 160kHz@-3dB
SNR	119dB@+24dB A-weighting, 123dB@+30dB A-weighting
THD+N	<0.02%@250W 8Ω in Stereo/Mono mode, <0.06%@500W 8Ω in Bridged mode
Crosstalk	-125dB
Gain	+24dB/+30dB
Speaker Impedance	Stereo/Mono mode 2-16Ω, Bridged mode 4-16Ω
Damping Factor	350@8Ω 1kHz

Trigger

Trigger in	DC 6-12V <10mA
Trigger out	DC 12V/50mA MAX

Power Specs

Power Voltage	AC 100V-120V 50/60Hz or AC 220V-240V 50/60Hz Factory fixed
Standby Power Consumption	< 1W
Idle Power Consumption	250-350W
Maximum Power Consumption	< 1250W

Weight & size

Weight	42.4kg (93.5 pounds)
Dimensions	Width: 430 mm (16.93 inches)
	Depth: 518 mm (20.39 inches)
	Height: 201 mm (7.91 inches)

Accessory

- Power cable x 1
- Trigger cable x 1
- User manual x 1
- Warranty card x 1