GE Zoneline® Heat Pump Unit with Makeup Air, 230/208 Volt



Model# AZ65H12DBM



- Product built to order, lead times may vary
- Makeup air Delivers 25-50 CFM of continuous makeup air whenever the room is occupied
- Energy efficiency When paired with occupancy sensing hardware, ventilation can be halted during vacancy
- Dehumidification Dehumidifies at a rate of 5-6 pints per 24 hours (based on CFM level)
- Boost heat option Provides supplemental resistance heat in heat pump mode
- Heat & Freeze Sentinels Keeps the room from overheating or freezing
- Electronic temperature limiting Prevents expensive over-cooling or over-heating of the room
- Electronic touch controls with LED display
- May reduce the need for individually ducted rooftop systems
- Because makeup air increases room BTU load requirements and requires additional PTAC cooling or heating, the building's electrical needs may be impacted
- Makeup air models are not recommended for installation within two miles of coastal areas
- It is strongly recommended to install makeup air with wall thermostats
- SMC base pan
- A Simplified structure Fasu to maintain and sorvice Have more questions? Please contact 1-800-626-2005

FEATURES Sensible Heat Ratio 69% Chassis Type Slide-In Control Type Standard Microcomputer; Tactile touch pad with LED Display Discharge Grille 2-position **Electronic Micro Computer Control** Yes Fan Cycle Switch Yes Fan Motor 2 Fan Speed Control Yes Fan Speed Selections Hi/Low Cooling; Hi/Low Fan Only; Hi/Low Heating Rigid Frame; Slide-Out Filter Tupe Heat - Cool Yes Reversible Louver Style **Rotary Compressor** Yes **Temperature Limiting** Electronic 7-Step **Zoneline Features** "Sleep" Mode; "Smart Fan" Fan Cycle Control; 3-Stage Heating Design; Auto Power Recovery; Automatic Emergency Heat; Automatic Indoor Frost Control; Central Desk Control Compatibility; Freeze Sentinel; Heat Pump with Resistance Heat Backup; Heat Pump with Supplemental Resistance Heat; Heat Sentinel; LCDI Power Cord; Proportional - Integral ID Airflow; Quick Heat Recovery; Random Twist/Length Segment Tangential Blower; Remote Thermostat Compatibility; Reverse Cycle Defrost; Universal Heaters; Weather Protected

Temperature Range

Electrical Components

60 - 85 F

GE Zoneline® Heat Pump Unit with Makeup Air, 230/208 Volt



Model# AZ65H12DBM

APPROXIMATE DIMENSIONS (HxDxW)

• 16 in x 20 13/16 in x 42 in

CAPACITY

- Cooling BTUH (MIN) 11400.00 Btu
- Cooling BTUH (MAX) 11500.00 Btu
- Cooling EER (BTUH / Watt) 11.2/11.2
- CFM Indoor Fan High 449
- CFM Indoor Fan Low 300
- Dehumidification (pts./hr.) 3.40
- Heating Reverse Cycle BTUH 10200/10000
- Vent CFM (high fan at zero ESP) 25-50

WARRANTY

- Parts Warranty Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
- Labor Warranty Limited 1-year entire appliance;
 Limited 5-year sealed refrigerating system
- Warranty Notes See written warranty for full details