

Product data sheet

CONSTRUCTION TYPE AND DESIGN

Combi-Steam Oven	•
PureLine	•
PureLine	•
Combi-Steam Oven	•
Appliance colour	CleanTouch Steel

CONVENIENCE FEATURES

Miele Mix & Match	•
Rapid PreHeat	•
Rapid PreHeat	•
Preheating	•
Preheating	•
External steam generation	•
External steam generation	•
Oxygen sensor	•
Oxygen sensor	•
Individual humidity settings in combination cooking	•
Individual humidity settings in combination cooking	•
Menu cooking without transfer of flavours	•
Menu cooking without transfer of flavours	•
Food probe	With cable

MasterChef programs with ability to make individual adjustments	•
--	---

MasterChef programs with ability to make individual adjustments	•
--	---

Keeping warm	•
---------------------	---

Keeping warm	•
---------------------	---

Crisp function	•
-----------------------	---

Crisp function	•
-----------------------	---

OPERATING MODES

Convection Bake	•
------------------------	---

Convection Roast	•
-------------------------	---

•

Combination cooking	•
----------------------------	---

Combination cooking with Convection Bake	•
---	---

Combination cooking with Surround	•
--	---

Combination cooking with Maxi Broil	•
--	---

Steam cooking	•
----------------------	---

Sous-vide	•
------------------	---

Maxi Broil	•
-------------------	---

Intensive	•
------------------	---

Humidity Plus	•
----------------------	---

Surround	•
-----------------	---

Browning	•
-----------------	---

Bake	•
-------------	---

Convection Broil	•
-------------------------	---

Special modes	•
----------------------	---

Defrost	•
----------------	---

MasterChef programs	•
----------------------------	---

MasterChef programs	•
Country-specific MasterChef programs	•
Country-specific MasterChef programs	•
Combination cooking with Convection Bake	•
Combination cooking	•
Combination cooking with Surround	•
Combination cooking with Maxi Broil	•
Steam cooking	•
Sous-vide	•
Reheat	•
Reheat	•
Roast with moisture	•
Roast with moisture	•
Maxi Broil	•
Broil	•
Broil	•
Intensive	•
Humidity Plus	•
Surround	•
Browning	•
Bake	•
Convection Broil	•
Plate warming	•
Plate warming	•
Special modes	•
Broiling operating modes	•
Broiling operating modes	•

USER CONVENIENCE

Clear text on control panel	•
Display	M Touch
SoftOpen	•
SoftOpen	•
SoftClose	•
SoftClose	•
Language Options	•
Language Options	•
MyMiele	•
MyMiele	•
Help function	•
Help function	•
Motorized lift-up control panel	•
Motorized lift-up control panel	•
Quantity-independent cooking	•
Quantity-independent cooking	•
Steam cook simultaneously on up to 4 levels	•
Steam cook simultaneously on up to 4 levels	•
Automatic menu cooking	•
Automatic menu cooking	•
Steam reduction before end of program	•
Steam reduction before end of program	•
Polyphonic audible signals	•
Polyphonic audible signals	•
Time-of-day display	•
Time-of-day display	•

Date display	•
Date display	•
Timer	•
Timer	•
Programmable start of cooking duration	•
Programmable start of cooking duration	•
Programmable end of cooking duration	•
Programmable end of cooking duration	•
Programmable cooking duration	•
Programmable cooking duration	•
Actual temperature display	•
Actual temperature display	•
Desired temperature display	•
Desired temperature display	•
Audible signal when desired temperature is reached	•
Audible signal when desired temperature is reached	•
Recommended temperatures	•
Recommended temperatures	•
Favourites	•
Favourites	•
Sabbath Program	•
Sabbath Program	•
Individual settings	•
Individual settings	•
Networking with Miele@home	•
Networking with Miele@home	•
Display	M Touch

Timers

•

Timers

•

MotionReact DG

•

MotionReact DG

•

CLEANING CONVENIENCE**Maintenance programs**

•

Maintenance programs

•

Stainless steel / Clean Touch Steel surface

•

Stainless steel oven compartment with linen-weave pattern and PerfectClean finish

•

External steam generator

•

Automatic descaling

•

CleanGlass door

•

Stainless steel / Clean Touch Steel surface

•

Stainless steel oven compartment with linen-weave pattern and PerfectClean finish

•

Hinged broiler

•

Hinged broiler

•

External steam generator

•

Condensate bottom heater

•

Condensate bottom heater

•

Separate soak

•

Separate soak

•

Rinse program

•

Rinse program

•

Oven compartment drying program

•

Oven compartment drying program

•

Quick-release side racks

•

Quick-release side racks

•

Removable side racks

•

Removable side racks

•

Descaling

•

CleanGlass door

•

STEAM TECHNOLOGY AND WATER SUPPLY**MultiSteam**

•

DirectWater plus

•

MultiSteam

•

DirectWater plus

•

Drain filter

•

Drain filter

•

SAFETY**Appliance cooling system with touch-cool fronts**

•

Safety shut-off

•

System lock

•

Appliance cooling system with touch-cool fronts

•

Safety shut-off

•

System lock

•

Steam cooling system

•

Steam cooling system

•

Sensor lock

•

Sensor lock

•

TECHNICAL DATA

Replacing lamps	Customer Service
Oven mode temperatures in °F (°C)	85-575 °F (30-300 °C)
Oven interior lighting	BrilliantLight
Number of shelf levels	4
Numbered shelf levels	•
Numbered shelf levels	•
Oven interior lighting	BrilliantLight
Niche width min. in inches (mm)	22 1/8 (560)
Niche width min. in inches (mm)	560
Niche width max. in inches (mm)	22 3/8 (568)
Niche width max. in inches (mm)	568
Niche height min. in inches (mm)	590
Niche height min. in inches (mm)	23 1/4 (590)
Niche height max. in inches (mm)	23 1/2 (595)
Niche height max. in inches (mm)	595
Niche depth in mm	21 7/8 (555)
Niche depth in mm	555
Appliance width in mm	595
Appliance width in mm	23 1/2 (595)
Appliance height in mm	23 1/2 (596)
Appliance height in mm	596
Appliance depth in mm	22 3/8 (567)
Appliance depth in mm	567
Weight in lbs (kg)	104 (47.1)
Weight in lbs (kg)	104 (47.1)
Weight in lbs (kg)	103.84 (47.1)

Total rated load in kW	2.800-3.700
Total rated load in kW	2.800-3.700
Voltage in V	0
Voltage in V	0
Usable voltage range in V	240/208
Usable voltage range in V	240/208
Frequency in Hz	60
Frequency in Hz	60
Fuse rating in A	20
Fuse rating in A	20
Number of phases	2
Number of phases	2
Power cable with plug	•
Length of power cable in m	2
Length of power cable in m	2
Length of water inlet hose in m	3.0
Length of water inlet hose in m	9 (3.0)
Length of water drain hose in m	9 (3.0)
Length of water drain hose in m	3.0
Appliance dimensions (W x H x D) in mm	23 1/2 (595) x 23 1/2 (596) x 22 3/8 (567)
Appliance dimensions (W x H x D) in mm	23 1/2 (595)<NBSP/>x<NBSP/>23 1/2 (596) <NBSP/>x<NBSP/>22 3/8 (567)
Niche dimensions (W x H x D) in mm	560-568 x 590-595 x 555
Door hinging	Bottom

ACCESSORIES SUPPLIED

FlexiClip Runners with PerfectClean (pair)	1
Universal tray with PerfectClean	1

Universal tray with PerfectClean	1
Wire rack with PerfectClean	1
Wire rack with PerfectClean	1
FlexiClip Runners with PerfectClean (pair)	1
Removable side racks with PerfectClean (pair)	1
Removable side racks with PerfectClean (pair)	1
Perforated stainless-steel cooking containers	2
Perforated stainless-steel cooking containers	2
Solid stainless-steel cooking containers	1
Solid stainless-steel cooking containers	1
Descaling tablets	2
Descaling tablets	2

AVAILABLE DISPLAY LANGUAGES

Available display languages via Language Options	bahasa malaysia
--	-----------------