# CLW-SWEX-230-P

# Cameo® Wireless In-Wall Switch, 230V

- > Field replaceable and engravable buttons
- > Available in all designer colors
- > infiNET EX® robust communication
- > Models popular Cameo® style
- > Configurable with rocker or two buttons
- > Matching aesthetics across entire line

The CLW-SWEX-230-P is a Cameo<sup>®</sup> wireless in-wall switch which features field-replaceable and engravable buttons. Available in designer colors and configurable with two buttons or in a rocker layout, the CLW-SWEX-230-P is more versatile than previous generations of in-wall switches. Its streamlined design matches the entire line of Cameo dimmers, switches and keypads, making it a great addition to new or retrofit installations. In addition to its attractive look and feel, infiNET EX<sup>®</sup> communication technology brings proven reliability to the CLW-SWEX-230-P.

## **Field-Replaceable Button Faces**

Like their cousin Cameo keypads, the buttons on the CLW-SWEX-230-P can be swapped in the field, making it easy to change engraving or color after installation. The rocker controller brings a familiar user interface to the Crestron<sup>®</sup> in-wall switch, while the two-button layout offers clear on/ off control.

### **Custom Programmable Keypad**

Because the CLW-SWEX-230-P is attached to the Crestron network, it can also function as a keypad, sending commands to trigger whole-room or house lighting scenes, or any other function. The two-button layout takes advantage of prime single-gang wall box real estate. Use buttons to control in-room audio or lamps. Press-and-hold and double-tap functionality allows buttons to be used for more than just one function.

#### infiNET EXÆ Communications

Ultra-reliable infiNET EX wireless technology provides steadfast 2-way RF communications throughout a residential or commercial structure without the need for physical control wiring. Employing a 2.4 GHz mesh network topology, each infiNET EX device functions as an expander, passing command signals through to every other infiNET EX device within range (approximately 150 feet or 46 meters indoors), ensuring that every command reaches its intended destination without disruption<sup>[1]</sup>.

The CLW-SWEX-230-P communicates with a Crestron control system via an infiNET EX Wireless Gateway (model CEN-RFGW-EX, DIN-AP3MEX, or MC3<sup>[2]</sup>). Up to 100 infiNET EX devices may coexist on a single wireless



network, and every device that is added to the network effectively increases the range and stability of the entire network by providing multiple redundant signal paths<sup>[1]</sup>. Built-in Dynamic Frequency Allocation continuously monitors RF conditions, automatically selecting the clearest channel to prevent interference from neighboring networks, cordless phones, and microwaves.

# **SPECIFICATIONS**

#### Load Ratings

Load Types: Incandescent, Magnetic Low Voltage, Electronic Low Voltage, and Fluorescent Ballast Minimum Load: 10 W Maximum Load: 1200 W/VA

#### **Power Requirements**

230 Volts AC, 50/60Hz, line power

#### Controls

Rocker switch or two-button configuration

## LED Indicator

Feedback: (1) White LED



Due to differences in monitors, actual colors may vary from colors as they appear onscreen.



#### Wireless

**RF Transceiver:** infiNET EX<sup>®</sup> 2-way RF, 2.4 GHz ISM Channels 11-26 (2400 to 2483.5 MHz), default channel 15; IEEE 802.15.4 compliant **Range (typical):** 150 ft (46 m) indoor, 250 ft (76 m) outdoor to nearest mesh network device(s); subject to site-specific conditions and individual device capabilities<sup>[1]</sup>

Gateway: Requires an infiNET EX gateway<sup>[2]</sup>

#### Connections

Line: Brown wire, 1.5 mm<sup>2</sup> (16 AWG) Neutral: Blue wire, 1.5 mm<sup>2</sup> (16 AWG) Load: Red wire, 1.5 mm<sup>2</sup> (16 AWG) Ground: Green/Yellow wire, 1.5 mm<sup>2</sup> (16 AWG)

#### Environmental

Temperature: 32° to 104°F (0° to 40°C) Humidity: 10% to 90% RH (non-condensing)

#### Enclosure

1-gang mountable in a 3-1/2 inch deep electrical box; Requires decorator style faceplate (not included)

#### Dimensions

Height: 4.13 in (105 mm) Width: 1.75 in (45 mm) Depth: 1.75 in (45 mm)

## Weight

5 oz (142 g)

# **MODELS & ACCESSORIES**

#### Available Models

CLW-SWEX-230-P-A-S: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Almond Smooth

CLW-SWEX-230-P-A-T: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Almond Textured

CLW-SWEX-230-P-B-S: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Black Smooth

CLW-SWEX-230-P-B-T: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Black Textured

CLW-SWEX-230-P-BRN-S: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Brown Smooth

**CLW-SWEX-230-P-DA-S:** Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Dark Almond Smooth

CLW-SWEX-230-P-DSK-T: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Dusk Textured

CLW-SWEX-230-P-GRY-S: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Gray Smooth

CLW-SWEX-230-P-IVR-S: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Ivory Smooth

CLW-SWEX-230-P-LAT-T: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, Latte Textured

CLW-SWEX-230-P-W-S: Cameo® Wireless In-Wall Switch, 230V, White Smooth

CLW-SWEX-230-P-W-T: Cameo<sup>®</sup> Wireless In-Wall Switch, 230V, White Textured

Notes:

- Any infiNET EX device that provides expander functionality will effectively extend the range of the wireless network beyond the initial range of the gateway. Battery-powered infiNET EX devices do not provide expander functionality. A dedicated infiNET EX Wireless Expander, model CLW-EXPEX or GLA-EXPEX, is also available.
- 2. Item(s) sold separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, Cameo, and infiNET EX are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

## **CAD DRAWING**

