

Specifications

1 model	WH-1000XM6
COLOUR	<input type="checkbox"/> Midnight Blue <input type="checkbox"/> Black <input type="checkbox"/> Platinum Silver
Summary PRICE	\$599.99 ¹
WHAT'S IN THE BOX	Carrying Case Connection Cable Reference Guide USB Cable Warranty Card
Size & Weight WEIGHT	Approx. 254 g
General Features HEADPHONE TYPE	Closed
DRIVER UNIT	30 mm
MAGNET	Neodymium
IMPEDANCE (OHM)	48 ohm (1 kHz) (when connecting via the headphone cable) 32 ohm (1 kHz) (when connecting via the headphone cable with the u
FREQUENCY RESPONSE	4–40,000 Hz (JEITA)
FREQUENCY RESPONSE (ACTIVE OPERATION)	4–40,000 Hz (JEITA)

1 model	WH-1000XM6
FREQUENCY RESPONSE (BLUETOOTH® COMMUNICATION)	20–20,000 Hz (44.1 kHz sampling) 20–40,000 Hz (LDAC C
SENSITIVITIES (DB/MW)	103 dB/mW (when connecting via the headphone cable wi (when connecting via the headphone cable with the unit tu
CORD TYPE	Single-sided (detachable)
CORD LENGTH	Approx. 1.2 m
PLUG	Gold-plated L-shaped stereo mini plug
INPUT(S)	Stereo Mini Jack
WEARING STYLE	Over Ear
MULTIPOINT CONNECTION	Yes
DSEE EXTREME	Yes
PASSIVE OPERATION	Yes
AMBIENT SOUND MODE	Yes
UNIT OF MICROPHONE	MEMS
DIRECTION OF MICROPHONE	Omni directional
Battery BATTERY CHARGE TIME	Approx. 3.5 hrs
BATTERY CHARGE METHOD	USB

1 model	WH-1000XM6
BATTERY LIFE (CONTINUOUS MUSIC PLAYBACK TIME)	Max. 30 hrs (NC ON), Max. 40 hrs (NC OFF)
BATTERY LIFE(CONTINUOUS COMMUNICATION TIME)	Max. 24 hrs (NC ON), Max. 28 hrs (NC OFF)
Bluetooth® Specification BLUETOOTH® VERSION	Bluetooth Specification Version 5.3 ²
EFFECTIVE RANGE	Approx. 10 m
FREQUENCY RANGE	2.4 GHz band (2.4000–2.4835 GHz)
PROFILE	A2DP, AVRCP, HFP, HSP, TMAP, CSIP, MCP, VCP, CCP
SUPPORTED AUDIO FORMAT(S)	SBC, AAC, LDAC, LC3
SUPPORTED CONTENT PROTECTION	SCMS-T
Noise Cancelling PERSONAL NC OPTIMIZER	Adaptive NC Optimizer
ATMOSPHERIC PRESSURE OPTIMIZING	Yes
AMBIENT SOUND	Yes
AUTO AMBIENT SOUND	Yes
QUICK ATTENTION	Yes

