

k

ISA

c

Monitor Section	Picture size	6.95 inches(diagonal) wide
	W x H	156.6 mm x 81.6 mm , 6-3/16 x 3-3/16 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32, exFAT, NTFS
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24/32Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2, MPEG4 / WMV / H.264 / MKV
	Frequency response 192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	98.5dB
Wireless Mirroring Section	Dynamic range	89dB
	Mode	Sink
	Copyright protection	HDCP2.2

Monitor Section	Picture size	6.95 inches(diagonal) wide
	W x H	156.6 mm x 81.6 mm , 6-3/16 x 3-3/16 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32, exFAT, NTFS
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24/32Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2, MPEG4 / WMV / H.264 / MKV
	Frequency response 192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	98.5dB
	Dynamic range	89dB
Wireless Mirroring Section	Mode	Sink
	Copyright protection	HDCP2.2

Monitor Section	Picture size	6.95 inches(diagonal) wide
	W x H	156.6 mm x 81.6 mm , 6-3/16 x 3-3/16 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32, exFAT, NTFS
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24/32Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2, MPEG4 / WMV / H.264 / MKV
	Frequency response 192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	98.5dB
	Dynamic range	89dB
Wireless Mirroring Section	Mode	Sink
	Copyright protection	HDCP2.2

Monitor Section	Picture size	6.95 inches(diagonal) wide
	W x H	156.6 mm x 81.6 mm , 6-3/16 x 3-3/16 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32, exFAT, NTFS
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24/32Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2, MPEG4 / WMV / H.264 / MKV
	Frequency response 192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	98.5dB
Wireless Mirroring Section	Dynamic range	89dB
	Mode	Sink
	Copyright protection	HDCP2.2



Monitor Section	Picture size	6.95 inches(diagonal) wide
	W x H	156.6 mm x 81.6 mm , 6-3/16 x 3-3/16 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32, exFAT, NTFS
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24/32Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2, MPEG4 / WMV / H.264 / MKV
	Frequency response 192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	98.5dB
Wireless Mirroring Section	Dynamic range	89dB
	Mode	Sink
	Copyright protection	HDCP2.2

Marina

Amplificare

Support

JA

Monitor Section	Picture size	6.95 inches(diagonal) wide
	W x H	156.6 mm x 81.6 mm , 6-3/16 x 3-3/16 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
USB I/F Section	USB Standard	USB2.0 High Speed
	File System	FAT 16/32, exFAT, NTFS
	Maximum Power Supply Current	DC5V=1.5A
	D/A Converter	24/32Bit
	Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2, MPEG4 / WMV / H.264 / MKV
	Frequency response 192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	98.5dB
	Dynamic range	89dB
Wireless Mirroring Section	Mode	Sink
	Copyright protection	HDCP2.2