Specs & Details

Dimensions: 34 H x 23 13/16 W x 25-3/16 D

APPEARANCE

Color Appearance	Fingerprint Resistant Stainless
Control Panel Color	Grey
Door Appearance	2 Drawer Fronts
Door Style	2 Drawer Fronts
Handle	Pocket Handle\nTreated with Microban™ Antimicrobial Techno
Handle Color	Recessed
Handle Design	Recessed
Installation	Side Installation or Top Installation Included Built-Up Floor Capable Flush Cabinet Installation
ECONOMICAL / QUIET	

ECONOMICAL / QUIET

Door Insulation	Yes
Motor Type	Variable Speed, BLDC
Outer Wrap	Full Steel Inclosure

Quiet Package	45 dBA Single/ 48 dBA Double		
FEATURES	FEATURES		
Active Flood Protection	Active Flood Protect		
Additional Protection	Active Flood Protect		
Control Type	Front Controls Cap Touch Controls 5 Touchpads		
Dishwasher Control Features	Delay and Lock capabilities, Audible End-of-Cycle Signal; Las		
Dishwasher Cycles	Heavy Normal Light 30 Minute Rinse Custom		
Dishwasher Drying Features	Fan Assist Dry		
Dishwasher Options	Extra, Normal, Off, Sanitize; Lock Controls, Delay		
Dispenser	Rinse Aid		
Exterior Style	Traditional		

Pull with Microban Treated Pocket Handle \nInterior lid closes

Latch

Leveling System	4 Leveling Legs
Lower Drawer	Standard 4 Utility Shelves; 2 with StemSafe Fold Down Tines Silverware Basket with cell covers and Microban treated hand Lower drawer fits 10-1/2 inch plates
Number of Cycles	6
Number of Options	4
Number of Place Settings	14
Product Type	Dishwasher Drawer
Rack Color	Silver Dust
Rack Features	Ball-Tipped Tines Full Extension Slides 2 long and 2 short articulating plastic utility shelves w/Stemsa Basket
Racking Material	Nylon
Racking System	2 Racks with 4 Cup Shelves
Showroom Power Mode	Yes
Style	Dishwasher Drawer

Tub and Door Liner	Gray Plastic	
Tub Type	Double Drawer	
Upper Drawer	Large 4 Utility Shelves; 2 with StemSafe Fold Down Tines Silverware Basket with cell covers and Microban treated hand Upper drawer fits 13 inch plates	
Wash Arms	2 Total, 1 per Drawer	
Wash System	2 completely independent wash systems	
Wash System Features	Single pump per sytem (identical per drawer); Water and Prim Automatic Temperature Control	
Water Filtration System	100% Filtration	
POWER / RATINGS		
Calrod Heater Watts	503	
Power Connection	Power Cord - Included	
Volts/Hertz/Amps	120V/60hz/9.4amp	
WARRANTY		
Labor Warranty	Limited 1-year entire appliance	

Parts Warranty	Limited 1-year entire appliance	
WEIGHTS & DIMENSIONS		
Approximate Shipping Weight	125 lb	
Cabinet Width	24 in	
Cutout Height (in)	34 in	
Depth with Door Open	21 9/16 in	
Depth Without Handle	22 3/4 in	
Height w/ Legs Retracted - Minimum Height	34 in	
Height w/Legs Extended - Maximum Height	36.375 in	
Net Weight	120 lb	
Overall Depth	25-3/16 in	
Overall Depth with Handle	22 3/4 in	
Overall Height	34 in	
Overall Width	23 13/16 in	