

Precision
sound

CC 550 IP

The Sennheiser CC 550 IP top-of-the-line headset offers precision sound to both ears for optimal understanding.

The highly durable construction is suited to all office and professional communication tasks.

This wideband headset delivers a more nuanced soundscape where voice transmission is perceived as warmer and more natural.

Use CC 550 IP for VoIP communication via softphones on PCs / MacBooks and IP desk phones.



- **HD voice clarity** The CC 550 IP wideband headset delivers natural high-definition sound for superior voice clarity, accented speaker recognition, and reduced echo
- **Boosted productivity** The binaural headset blocks background noise, allowing total concentration for increased productivity
- **Superior fit** Independently adjustable dual-padded headband and ball-mounted speakers ensure a perfect fit
- **Precision positioning** 300° adjustable microphone boom for personalised mic placement
- **Optimum clarity** An ultra noise-cancelling microphone filters out ambient sounds for clearer speech
- **Protected hearing** ActiveGard® technology protects against acoustic shock and sudden sound surges
- **Extra comfort** Generous headband padding and extra large ear pads evenly distribute pressure for longer lasting comfort – guaranteed

Specifications

| | |
|---|---------------------------------------|
| Headset | CC 550 IP |
| EAN No. (GTIN-13) | 40 44155 04671 7 |
| UPC No. | 6 15104 17285 2 |
| Art. No. | 504017 |
| Technical data | |
| Weight, headset | 100 g |
| Weight, headset, cable and connector | 110 g |
| Package dimensions | 175 x 162 x 58 mm |
| Package weight | 260 g |
| Units in distributor master carton | 20 |
| Weight master carton | 6.4 kg |
| Dimensions master carton | 370 x 330 x 380 mm |
| Wearing style | Headband, binaural (double sided) |
| Microphone | Ultra noise canceling |
| Frequency response | 150 Hz – 6800 Hz |
| Distortion | Less than 1% |
| Speaker | |
| Impedance | ~180 Ω |
| Frequency response | 150 Hz – 6800 Hz |
| Sound pressure | Max. 103 dB limited by ActiveGard® |
| All acoustic parts observe the TIA-920 wideband standards | |
| Ear cap size | Extra large ϕ 51 mm / 2.0 inches |
| Cable length | 1 m / 3.3 ft Vectran™* reinforced |
| Connector | Easy Disconnect |
| *Vectran™ is a registered trademark of Kuraray Co., Ltd., Japan | |
| Accessories included | |
| Acoustic foam ear pads | |
| Carry bag | |
| Clothing clip | |
| Coloured ID clips (3) | |
| Leatherette ear pads | |
| Microphone windscreen | |