

ILVE

Range cookers → Panoramagic

UPM09



Colour range

Body



Stainless steel – SS

Finishes



Satin

Available ovens


Electric oven

Primary oven:
UOV 80 E3 TFT S


Maximum input:
3.7 kW

Configurations

6 burners with fry top*



Induction



Electric oven

UPM09FDS3

Brushed

UPMI09S3

Brushed

Fuel requirements

Natural gas / Liquid propane

Voltage: 240 Volts

Amps: 18.1

All electric

Voltage: 240 Volts

Amps: 66

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

Bridge induction zone
Ø 7" 1/4 + Ø 7" 1/4
1.85 / 2.5 kW + 1.85 kW

Induction zone
Ø 5" 3/4
1.4 / 1.8 kW

Induction zone
Ø 7" 1/4
1.85 / 2.5 kW

Induction zone
Ø 8" 11/16
2.3 / 3.2 kW

Double ring Dual burner
20000 btu/h / 900 btu/h

Double ring burner
16500 btu/h / 6200 btu/h

Griddle
10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h

Big burner
10500 btu/h / 2000 btu/h

Small burner
7000 btu/h / 1400 btu/h

Complements & accessories

Hood

UAPM90

Backsplash panel

AM4-90

Brushed

Technical drawing & dimensions

