Technical Specifications
Evo 150

POWER OUTPUT
150W into 8 Ohms

AMPLIFICATION
Class-D

DAC
ESS Sabre ES9018K2M

THD
0.0011% 1kHz at 1W, 20Hz - 20kHz BW

FREQUENCY RESPONSE
20Hz –20kHz +/-3dB

S/N ratio
(ref full power) >104dB (unweighted)

ANALOGUE AUDIO INPUTS
1 x RCA, 1 x Balanced XLR, 1 x MM Phono

DIGITAL AUDIO INPUTS
2 x TOSLINK optical, 1 x S/PDIF coaxial, Bluetooth (integrated), 1 x TV ARC, USB Audio

USB Audio: USB Type B conforming to USB Audio Class 1 or USB Audio Class 2
Bluetooth: 4.2 A2DP/AVRCP supporting SBC, aptX and aptX HD codecs

COMPATIBILITY
TOSLINK optical: 16/24bit 32-96kHz PCM only
S/PDIF coaxial: 16/24bit 32-192kHz PCM only
ARC: 16/24bit 32-192kHz PCM only
USB Audio Class 1: Up to 24-bit 96kHz (asynchronous)
USB Audio Class 2: Up to 24-bit 384kHz (asynchronous) and up to DSD-256

UPnP, Local USB media, Airplay 2, Chromecast built-in, Internet Radio, Spotify Connect, TIDAL, Qobuz, Deezer, RoonReady.

Note: USB media maximum current 1A

AUDIO FORMATS
ALAC, WAV, FLAC, AIFF, DSD (x256), WMA, MP3, AAC, HE AAC AAC+, OGG Vorbis

OUTPUTS
Speakers A+B, 3.5mm headphone, Preamp Output, Subwoofer Output, Bluetooth (integrated)

Bluetooth: 4.2 A2DP/AVRCP supporting up to aptX HD

ETHERNET
IEEE 802.3, 10 Base-T or 100 Base-T

WI-FI
Dual-Band 2.4/5GHz

MAX POWER CONSUMPTION
700W

STANDBY POWER CONSUMPTION
<0.5W

DIMENSIONS (W x H x D)
317 x 89 x 352 mm

WEIGHT
5.3Kg