# FRIGIDAIRE.



UL Listed

30" Electric Range

Coil Range

Available Products: FCRC3012BB, FCRC3012BS, FCRC3012BW

Available Colors: Black, Stainless Steel, White

Version: 07/25

## **Product Specifications**

Cooking Controls		Oven	
Bake	Yes	Bake Element	2600 Watts
Broil	Yes	Bake Element Pass	4
Kitchen Timer	Yes	Bake Element Type	Raised
Off	Yes	Broil Element	3000 Watts
Oven Light	Yes	Broil Element Pass	4
Preheat	Yes	Number of Rack Positions	6
Temperature Display	Yes	Oven Interior Color	Midnight Black
Timer On / Off	Yes	Oven Light Quantity	1
Up / Down Arrow	Yes	Oven Light Type	Halogen
		Oven Light Watts	40 Watts
Cooktop		Rack Position Type	Embossed
Cooking Surface Type	Coil	Rack Type 1	Flat
Drip Bowl Type	Porcelain	Rack Type 1 Quantity	2
Drawer		Cooktop Performance	
Drawer Handle Style	Integrated	Right Front Element Burner Size	6"
Drawer Type	Storage	Right Rear Element Burner Size	8"
J 1	Ö	Left Front Element Burner Size	8"
Dimensions and Volume		Left Rear Element Burner Size	6"
Minimum Height	46 3/4"	Right Front Element Burner	1500 Watts
Maximum Height	47 3/4"	Right Rear Element Burner	2400 Watts
Width	30"	Left Front Element Burner	2400 Watts
Depth	26"	Left Rear Element Burner	1500 Watts
Depth With Door 90° Open	47 5/16"		
Depth With Handle	28 1/2"	Display	
Oven Interior Height	18 1/8"	Control Location	Rear
Oven Interior Width	25 3/16"	Display Interface Color	White
Oven Interior Depth	19 7/8"	Display Type	Tactile
Oven Capacity	5.3 Cu. Ft.		
1 - 7		Installation	
General Specifications		Adjustable Leveling Legs	Yes
Prop 65 Label	Yes		
Warranty - Labor	1 Year	Certifications and Approvals	
Warranty - Parts	1 Year	ADA Compliant	No

Yes

Available Products: FCRC3012BB, FCRC3012BS,

FCRC3012BW

Version: 07/25


Available Colors: Black, Stainless Steel, White

### **Installation Diagram**

#### 30" ELECTRIC REAR CONTROL FREESTANDING INSTALLATION INSTRUCTIONS

#### 1. Clearances and Dimensions

- a. Provide adequate clearances between the range and adjacent combustible surfaces.
- b. Location—Check location where the range will be installed. Check for proper electrical supply and the stability of floor.
- c. Dimensions that are shown must be used. Given dimensions provide minimum clearance. Contact surface must be solid and level.






Fig. 2

\*30" (762 mm) MINIMUM CLEARANCE BETWEEN THE TOP OF THE COOKING SURFACE AND THE BOTTOM OF AN UNPROTECTED WOOD OR METAL CABINET, OR 24" (610 mm) MINIMUM WHEN BOTTOM OF WOOD OR METAL CABINET IS PROTECTED BY NOT LESS THAN 1/4" (6 mm) FLAME RETARDANT MILLBOARD COVERED WITH NOT LESS THAN NO. 28 MSG SHEET STEEL, 0.015" (0.4 mm) STAINLESS STEEL, 0.024" (0.6 mm) ALUMINUM OR 0.020" (0.5 mm) COPPER. 0" (0 mm) CLEARANCE IS THE MINIMUM FOR THE REAR OF THE RANGE. FOLLOW ALL DIMENSION REQUIREMENTS PROVIDED ABOVE TO PREVENT PROPERTY DAMAGE, POTENTIAL FIRE HAZARD, AND INCORRECT COUNTERTOP AND CABINET CUTS.

TO ELIMINATE THE RISK OF BURNS OR FIRE BY REACHING OVER HEATED SURFACE UNITS, CABINET STORAGE SPACE LOCATED ABOVE THE SURFACE UNITS SHOULD BE AVOIDED. IF CABINET STORAGE IS TO BE PROVIDED, THE RISK CAN BE REDUCED BY INSTALLING A RANGE HOOD THAT PROJECTS HORIZONTALLY A MINIMUM OF 5" (127 mm) BEYOND THE BOTTOM OF THE CABINETS.




Fig. 3