





## Installation Quick Start Guide for AQT-M2

Important Installation Instructions


- 1 Locate the filter cartridge holder in the back upper right hand corner of the refrigerator. To open the cartridge cover, push in where indicated and the cover will drop down.




- 2 Remove old filter by slowly rotating it to the left. A small amount of water may drip down.




- 3 Carefully remove the plug on top of the new filter (twisting it back and forth eases the plug out). Be careful not to remove the o-ring located under the plug. IF THE O-RING IS MISSING, PLEASE CALL (866) 218-8473 FOR HELP.




- 4 Position the cartridge inside the cartridge holder and slowly rotate the cartridge to the right until it stops. When the cartridge is properly installed, you will feel it "click" as it locks into place. The blade on the end of the cartridge should be positioned vertically. Do not overtighten.



- 5 Close the cartridge cover.



- 6 Run water from the dispenser for 5 minutes at .5 gpm (about 2½ gallons) to clear the system and prevent sputtering.



- 7 Reset the "replace filter" light. Refer to your refrigerator owner's manual for reset procedure.

- 8 Attach the included water filter replacement calendar label according to the label instructions.

For further questions or assistance please call (866) 218-8473.  
Monday - Friday 8am to 5pm Pacific Standard Time

### WARNING

A newly-installed water filter cartridge may cause water to spurt from the dispenser until all the air is removed. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Protect from freezing.

To reduce the risk of property damage due to water leakage, this filter MUST be installed in accordance with the manufacturer's specifications and instructions. This filter must be replaced every 6 months, at the rated capacity, or sooner if reduced water flow occurs. Failure to follow instructions and operation specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product. The filter bypass plug MUST be used when a filter replacement cartridge is not installed.

The risk associated with small parts can cause choking if swallowed. Keep children away from small parts during the replacement of the water filter.