Product data sheet

CONSTRUCTION TYPE	
Door hinging	Left convertible
Convertible hinging	•
USER CONVENIENCE	
NoFrost	•
SoftClose	•
CONTROLS	
Eco mode	•
Independent temperature regulation of fridge and freezer compartments	•
Holiday mode	•
EFFICIENCY AND SUSTAINABILITY	
Energy Star	•
TECHNICAL DATA	
Replacing lamps	Customer Service
Number of phases	1
Niche width in inches (mm), min.	36 (914)
Niche width in inches (mm), max.	36 (914)

10/19/23, 2:32 PM KF 2912 SF | Miele

Niche height in inches (mm), min.	84 1/8 (2134)
Niche height in inches (mm), max.	84 1/8 (2134)
Niche depth in mm	24 1/8 (610)
Appliance width in mm	35 3/4 (908)
Appliance height in mm	83 3/4 (2125)
Appliance depth in mm	24 (608)
Weight in lbs (kg)	495 (224.3)
Door hinge technology	Fixed door
Total usable capacity in I	19.56 (554) ft³ (I)
Current consumption in milliamps (mA)	4000
Voltage in V	110-120
Fuse rating in A	10
Frequency in Hz	60
Length of power cable in m	11 (3.5)

APPLIANCE CATEGORY

Fridge / freezer

AVAILABLE DISPLAY LANGUAGES

Available display languages via Language Options

bahasa malaysia