

Speed Queen®

MULTI-HOUSING

Quantum® Rear Control
Commercial Washers & Dryers

COIN

CARD VEND



BUILT FOR **RELIABLE** PERFORMANCE.

Speed Queen's commitment to multi-housing laundry is unmatched anywhere else in the industry. Built for performance and reliability, our laundry machines maximize your profitability and provide unparalleled convenience for your property.

Speed Queen®'s line of washers and dryers are ready to meet the demands of your laundry room. They are designed to work as a single or stacked laundry setup, provide maximum energy efficiency and long-lasting performance.

EQUIPPED WITH QUANTUM CONTROLS TO PROVIDE:

Total automated management of your laundry room. Its simple, powerful programming gives you the ability to:

- Easily manage your laundry operation with remote internet access.
- Establish multi-level vend prices, soil level cycles and dryer top-off times on your machines.
- Track coin or card transactions.
- WashAlert™ with Service Alert capable.

ACTIVATION TYPES

Offering a variety of activation types allowing you to tailor your laundry room to fit your needs. Standard and high capacity meter case available.



Coin ("C")



Prep for Card ("Y")



Prep for Coin ("X")



TOP LOAD WASHER

Speed Queen top load washers offer customer conveniences and quality components.



FEATURES

HIGH SPEED EXTRACT

710 RPM final spin to maximize moisture removal from clothes.

AUTOMATIC BALANCING SUSPENSION SYSTEM

Rear self-leveling legs maximize smooth and quiet operation on all floor types.

DURABLE STAINLESS STEEL WASH TUB

Comes with a lifetime warranty, and actually becomes smoother with each use, so it won't pill, snag or fray clothes.



FRONT LOAD WASHER

The Speed Queen front load washer gives building owners and property managers unparalleled ability to reduce water and energy costs through advanced programmability.

FEATURES

REVOLUTIONARY BALANCING TECHNOLOGY

Improved out-of-balance technology that uses a redesigned suspension and advanced sensing to manage and redistribute out-of-balanced loads, delivering uninterrupted cycles.

STAINLESS STEEL WASH TUB

Comes with a lifetime warranty, and actually becomes smoother with each use, so it won't pill, snag or fray clothes.



LOW WATER USAGE

Per cycle to reduce operating costs.

HIGH SPEED EXTRACT

1200 RPM final spin exerts 440 G-Force to maximize moisture removal from clothes.

LARGER DOOR OPENING

Extra wide 15.5" (394 cm) for easy loading and unloading of clothes.

FOUR COMPARTMENT SUPPLY DISPENSER

Prewash, wash, fabric softener, bleach.



ENERGY STAR®
Certified Washer

SINGLE LOAD DRYER

Speed Queen rear control commercial dryers offer customer conveniences and quality components. Speed Queen's single load dryers combine heavy-duty construction with reliable operation proven to stand the test of time. They're designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road.

FEATURES

SUPERIOR DRYING CONVENIENCE

With a 2.06 sq. ft. (1914 cm²) door opening, making it the widest in the industry, Speed Queen dryers offer the convenience of easy loading and unloading.

EFFICIENT DRYER HEATING

25,000 BTU (gas models) and 5,350 Watts (electric models) provide fast drying and lower operating costs. Speed Queen dryers offer some of the fastest drying times in the industry. The perfect balance of heat, airflow and tumble action for optimal performance and efficiency.

UPFRONT LINT FILTER

Easy to clean and secured.

REVERSIBLE DOOR (SOLID DOORS ONLY)

For installation flexibility.



STACK DRYER

The Speed Queen stack dryer offers the same great features as the single load dryer. Two commercial dryers in the space of one, both operating independently, including independent controls for optimum usage. Available with see-through or solid door models. ADA Compliant (bottom dryer only).



QUANTUM® CONTROL COMMERCIAL WASHER & DRYER SPECIFICATIONS

MODELS and ACTIVATION {NOTE: Coin Box Sold Separately}	COIN	Top Load Washer	Front Load Washer	Single Load Dryer	Stack Dryer
		SWNNC2PP113TW01 SWNNC2SP113TW01 SWNNC2PP113TW02♦ SWNNC2SP113TW02♦	SFNNCRSP113TW01 SFNNCRSP113TW02♦	Electric 208: SDENCRGS153TW01 240: SDENCRGS173TW01 Gas: SDGNCRGS113TW01 Electric 240: SDENCRGS173TW02♦ Gas: SDGNCRGS113TW02♦	Electric 208: SSENACGS153TW01 240: SSENACGS173TW01 Gas: SSGNCAGS113TW01 Electric 208: SSENACAGW173TW01 240: SSGNCAGW113TW01 Gas: SSENYAGS153TW01 Electric 208: SSENYAGS173TW01 240: SSGNYAGS113TW01 Gas: SSEWYAGS153TW01♦♦ Electric 208: SSEWYAGS173TW01♦♦ 240: SSGWYAGS113TW01♦♦ Gas: SSENXAGW173TW01 Electric 240: SSGNXAGW113TW01 Gas: SSGNXAGW113TW01
	PREP CARD	SWNNY2PP113TW01 SWNNY2SP113TW01	SFNNYRSP113TW01 SFNWYRSP113TW01♦♦	Electric 208: SDENYRGS153TW01 240: SDENYRGS173TW01 Gas: SDGNYRGS113TW01 Electric 208: SDEWYRGS153TW01♦♦ 240: SDEWYRGS173TW01♦♦ Gas: SDGWYRGS113TW01♦♦	Electric 208: SSENYAGS153TW01 240: SSENYAGS173TW01 Gas: SSGNYAGS113TW01 Electric 208: SSEWYAGS153TW01♦♦ 240: SSEWYAGS173TW01♦♦ Gas: SSGWYAGS113TW01♦♦
	PREP COIN	SWNNX2SP113TW01 SWNNX2PP113TW02♦ SWNNX2SP113TW02♦	SFNNXRSP113TW02♦	Electric 240: SDENXRGS173TW01 Gas: SDGNXRGS113TW01 SDENXRGS173TW02♦ SDGNXRGS113TW02♦	
Porcelain or Stainless Basket/Cylinder Volume - cu.ft. (liters)		3.26 (92.3)	3.42 (96.8)	7.0 (198)	7.0 (198) (ea)
Width - in (mm)		25 5/8 (651)	26 7/8 (683)	26 7/8 (683)	26 7/8 (683)
Depth - in (mm)		28 (711)	27 3/4 (704)	28 (711)	28 (711)
Height - in (mm) standard capacity high capacity♦		43 (1092) 43 7/8 (111.44)	43 (1092) 43 7/8 (1114)	43 (1092) 43 7/8 (1114)	78 3/16 (1986)
Weight - lb (kg)		190 (86)	253 (114.8)	Electric: 135 (61) Gas: 140 (64)	Electric: 265 (120) Gas: 275 (125)
Shipping Weight - lb (kg)		210 (95)	273 (123.8)	Electric: 145 (66) Gas: 150 (68)	Electric: 280 (127) Gas: 290 (132)
Cycle Time - minutes (default)		27	27/45	45	45
Motor HP (Capacitor Start and Thermal Protected)		0.9 HP 671 W	0.9 HP 671 W	1/3 HP, 5.5 amps	1/3 HP, 5.5 amps
Water Consumption - gal (Liter)		24.6 (93.0)	11.7 (44.3)	N/A	N/A
Water Factor - gal/ft³ (Liters/Liter/cycle)		7.9 (1.06)	3.8 (0.52)	N/A	N/A
Modified Energy Factor ft³/kWh/cycle (Liters/kWh/cycle)		1.69 (47.89)	2.98 (84.48)	N/A	N/A
Average Hot Water Per Cycle - gal (Liter)		1.9 (7.0)	0.4 (1.4)	N/A	N/A
Water Pressure PSI (Bar)		20-120 (1.4-8.3)	20-120 (1.4-8.3)	N/A	N/A
Spin Speed - RPM		710	500, 800, 1200	N/A	N/A
Cycle / Temperature		Light, Medium, Heavy, Small Load, Normal, Perm Press, Delicates Hot, Warm, Cold	Normal, Perm Press, Delicates/Bulky	High 160 ° Medium 155 ° Low 145 ° Delicate 115 ° No Heat	High 160 ° Medium 155 ° Low 145 ° Delicate 115 ° No Heat
Electrical Specifications and Circuit Requirements		120/60/1-15 amp	120/60/1-15 amp	Electric: 208/60/1-30 amp 240/60/1-30 amp* Gas: 120/60/1-15 amp	Electric: 2 ea 208/60/1-30 amp 240/60/1-30 amp* Gas: 2 ea 120/60/1-15 amp
Btu per Hour (kcal)		N/A	25,000 (6300)	25,000 (6300)	25,000 (6300)
Heating Element**		N/A	N/A	Electric: 2 ea 4750W (208) 5350W (240)	Electric: 2 ea 4750W (208) 5350W (240)
Type of Gas (Gas models only)		N/A	N/A	Factory-equipped natural/mixed gas convertible to LP gas**	Factory-equipped natural/mixed gas convertible to LP gas**
Utility Connections - in (mm)		N/A	N/A	Gas: 3/8 NPT (9.5)	Gas: 3/8 NPT (9.5)
Air Outlet Diameter - in (mm)		N/A	N/A	4 (102)	4 (102)
Exhaust Airflow - cfm (liters/sec)†		N/A	N/A	220 (105)	220 (105)
Maximum Exhaust Static Back Pressure		N/A	N/A	0.6" W.C.	0.6" W.C.
Agency Approval		cCSAus	cCSAus	Electric: cULus Gas: cCSAus	Electric: cULus Gas: cCSAus
Activation		Coin/Card Op	Coin/Card Op	Coin/Card Op	Coin/Card Op
Top and Lid Finish		Porcelain	Porcelain	Porcelain	N/A
Colors		White	White	White	White
Door Type		N/A	N/A	Solid	Solid, Window
Drain		Pump	Pump	--	--
Wireless Network Board Installed		--		Yes	Yes

NOTE: Each stack dryer pocket requires its own separate power cord.

* Electric dryers come equipped for 240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit.
Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

** IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

† Measured at point of exit from dryer.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008. Printed in the U.S.A.



Speed Queen®