The Ispira Series offers bold modern design featuring 8 striking colors of interchangeable glass panels.

Exclusive PURLED™ light system: boosts light output by 25%, geable distributes light six times better and improves energy efficiency by 88%. Choice of standard white, grey and black glass colors or interchangeable optional color panels to help you personalize your kitchen décor.

Two ultra-efficient hybrid baffle filters, easy to clean, for optimal grease removal.

Model Numbers:

30"-WCB3I30SBB 36"-WCB3I36SBB

WCB3I30SBW WCB3I36SBW WCB3I30SBN WCB3I36SBN No Glass



Four-speed soft touch controls sit behind white, grey, black or optional glass panels to match appliance finishes or complement your kitchen décor.



PURLED™ light system boosts light output, distributes light better and improves energy efficiency.



Hybrid baffle filters provide ultra-efficient grease removal with superior air flow.

# Glass panels sold separately



Emerald, Lime, Orange, Purple, Red

#### **Hood Sizes** Widths 30", 36" Depth 20-3/4" Finish Stocked Brushed Stainless Steel (Grade 430) with white, black or grey glass Special Order Not Available Features PURLED™, 5.5 watts each, Lighting Type 1100 Lumens, 3000K 2 Number of Lamps Lighting Levels 3 Lighting Lamps Included Yes Control Type 4-speed Soft Touch Control Features Heat Sentry<sup>™</sup>, Delay-off

### **Hood Blower Included**

Non-ducted Capability

Internal		
Max Blower CFM*	650	
Sones Normal Setting**	1.4	

Νo

Not Available Hybrid Baffle

#### Accessories

Remote Control

Filter Type

10' Flue Extension AEWCB3SB
Glass Panels White, Grey, Black, Emerald, Lime,
Orange, Purple, Red


Installation Requirements

 Amps @ 120V
 3.3

 Electrical Connection
 Plug In

 Duct Size: Internal Blower
 3-1/4" x 10"

 Duct Direction
 Vertical / Horizontal



Installation height above the cooking surface: 24"-36"

Telescopic flue for 8'-9' ceiling is standard. Optional flue extension for 10' ceiling

For more details or HVI rated performance for this model see the product specifications sheet found at www.BESTRangeHoods.com



If needed, ask a recommended installer to limit discharge to 300 CFM.





<sup>\*</sup>MAX Blower CFM indicates the performance of the hood blower in open air.
\*\*Normal setting corresponds to speed 1.

## Performance is a beautiful thing.

It can be subtle or bold. It can take months or years to hone. Then impress you in an instant.

A great performance gives the audience exactly what they want and more than they ever imagined. And it inspires everyone and everything around it to be better.

At **BEST**, we make high performance range hoods that perform beautifully. Astonishingly quiet. Impressively effective. Remarkably efficient. And perfectly suited for the most distinguished kitchens.

Whether it's the centerpiece of the room or letting its surroundings shine, **BEST** is where high-end performance inspires.

