

Powered by the exclusive iQ Blower System™ with GPS Technology (see page 62) for the quietest, most energy efficient and fastest smoke and odor removal available in a range hood; external blowers offered separately.

Bright Halogen lighting floods the cooktop and surrounding area for clear visibility.

Mesh lined Hi-Flow™ baffle filters provide superior grease capture to ensure a clean, fresh kitchen.

Heat Sentry<sup>™</sup> detects excessive heat and adjusts blower to high automatically.

Works with optional Universal Make-Up Air Dampers.

## Model Numbers:

IPP9IQT42SB IPP9E42SI



Three-speed, plus boost, electronic controls include 10-minute delay-off and filter clean reminder.



Four Halogen lamps brightly illuminate the cooktop.



Hi-Flow™ baffle filters utilize a V-mesh & baffle design to increase airflow, decrease sound levels and provide excellent ventilation efficiency.



Optional ACR2 remote control lets the busy cook stay in control from anywhere in the kitchen.



Hood Sizes	
Width	42"
Depth	30"
Finish	
Stocked	Brushed Stainless Steel
Special Order	Not Available
Features	
Lighting Type	Halogen, T4, G-9, 25-watt
Number of Lamps	4
Lighting Levels	2
Lighting Lamps Included	Yes
Control Type	3-speed Plus Boost Electronic Pushbutton with Display
Control Features	Heat Sentry™, Delay Off, Filter Clean Reminder
Remote Control	Optional ACR2
Filter Type	Hi-Flow™ Baffle Filter
Non-ducted Capability	No

# Hood Blower Included (IPP9IQ)

Internal	iQ12	
Blower CFM	1200	
Sones Low/High	0.3/10.5	

# Hood Blower Options (IPP9E blowers sold separately)

External In-line	ILB3	ILB6	ILB9	ILB11		
Max CFM	280	600	800	1100		
Sone levels are typically half of comparable CFM internal blowers.						
External Exterior	EB6	EB9	EB12	EB15		
External Exterior Max CFM	<b>EB6</b> 600	<b>EB9</b> 900	<b>EB12</b> 1200	<b>EB15</b> 1500		

#### Accessories


Accessories		
10'-11' Flue Extension (Ducted)	AEIPP9SB	
Universal MUA Damper	MD6TU, MD8TU, MD10TU	

## **Installation Requirements**

Amps @ 120V: Internal Blower
Amps @ 120V: External Blower
Electrical Connection
Duct Size: Internal Blower
Duct Size: External Blower
Duct Direction
Duct Direction
Backdraft Damper

8.5
7.0 Max
Direct Wire
10"
(at hood)





Installation height above the cooking surface: 24"-36"

Telescopic flue for 8'-9' ceiling is standard. Optional flue extensions for 10'-11' ceiling

For more details see the product specifications sheet found at www.BESTRangeHoods.com