

**Color Variants** 

RF471701 Fully integrated appliance Width 30" (76.2 cm)

#### Included accessories

1 x ice cube scoop.

Optional accessories

RA450000

Mechanical particle filter

RA450010

Activated charcoal filter for water filter system including saturation indicator

Required installation accessories

RA460010

Additional side heating element

RA460020

Connecting element for vertically split appliance fronts (for a flush front)

# Installation Accessories

RA421710

Stainless steel door panel with handle

RA425110

Long stainless steel door handle

RA460040

Finger protection for extra long furniture fronts

RA461710

Ventilation grill, stainless steel

RA461711

Ventilation grill, stainless steel

RF471701 Freezer column Fully integrated appliance

Width 30" (76.2 cm)

Width 30" (76.2 cm) Fully integrated appliance Stainless steel interior Integrated automatic ice maker with fixed water connection Solid aluminum door bins Net volume 15.8 cu.ft. **ENERGY STAR® qualified** 

Electronic precision temperature control with digital temperature display.

#### Technical features

Dynamic cool air distribution with Multi-Flow Air System.

Automatic defrosting with defrost water evaporation.

Energy-saving vacation mode. Open-door and malfunction warning system.

## Freezer compartment

No-frost technology with fast freezing. Temperature adjustable from 7 °F to -9 °F (-14 °C to -25 °C).

4 solid metal shelves, three of which are manually adjustable.

2 fully extendable drawers with transparent front, one of which is large, one is regular. Bright interior lighting with LED sidewall

4 height-adjustable door bins, one of

which is a gallon door bin. 1 door bin with transparent front flap.

#### Ice dispenser

Integrated, with fixed water connection. Ice maker can be switched off independently.

Ice cube production approx. 3.9 lb (1.8 kg)/24 h.

Removable ice storage bin with approx. 8.8 lb (4 kg) capacity.

# Planning notes

Flat hinge.

Door hinge left, reversible Door opening angle of 115°, optional 90° door stop.

Shut-off valve for water connection must be planned next to the appliance and always be accessible.

If the water pressure exceeds 116 psi, connect pressure relief valve between water tap and hose set.

Cold water connection required. Electrical location 6" above ground in lower left corner of unit. Water pressure 29 to 116 psi.

# Consumption data

Energy consumption 1.545 kwh/24 h. Noise level 39 dB.

# Rating

Total rating 0.565 kW. Total Amps: 10 A. 120 V / 60 Hz Connecting cable 139 1/3" with plug. Supply hose 118" with 3/4" connection. **Product Features** 

**Multi-Flow Air Tower** 

Number of compressors

Number of independent cooling systems

Eco Mode

SUPERFREEZE

Number of Door Bins - Freezer

Adjustable Door Bins - Freezer

Tilt-Out Door Bins - Freezer

Number of Shelves - Freezer

Adjustable Door Bins - Freezer

Shelf Material - Freezer

Metal

Door Hinge

Left reversible

Reversible Door Hinge

#### Consumption and connection features

UPC code

825225900351

Variant color

Panel ready

Installation Type

Silence level (dBA)

Watts (W)

N/A

Current (A)

Volts (V)

Frequency (Hz)

Total annual energy consumption (kWh)

Energy Star® qualified

Approval certificates

ETL, ETL C

**Power Cord Length** 

Plug type

120V-3 prong

# Appliance dimensions (h x w x d) inch

83 3/4 " x 29 3/4" x 24

### Required cutout size (HxWxD) (in) x 84" x 29 3/4'

Appliance Width (in)

Height (in)

83 3/4

Depth (in)

## Product packaging dimensions (HxWxD) (in)

88.97 x 33.46 x 29.52

Total unit gross capacity (cu. ft.) - AHAM

Net weight (lbs)

Gross weight (lbs)


432


2017-08-24 Page 1



RF471701 Freezer column Fully integrated appliance Width 30" (76.2 cm) 2017-08-24

Page 2





The drawing is based on a cabinet panel width of  $^3/\epsilon^*$  (19 mm) and a Gaggenau cabinet handle height of  $1^9/\epsilon^*$  (49 mm).

