

Item # : LCFNBAWHAG26 / LCFNBAWHPB26 Fauna 26" Barstool


LCFNBAWHAG30 / LCFNBAWHPB30 Fauna 30" Barstool



Thank you for purchasing this quality product. Be sure to check all packing material carefully for small parts, which may come loose inside the carton during shipment . Please identify and count all parts and compare with the HARDWARE LIST below.



Caution : Please read instructions carefully before unpacking assembly parts. Sharp , exposed staples can cause injury , therefore , for your protection , please remove any exposed staples used in packing.

*** Retain the Allen key for regular maintenance. We recommend tightening all screws every three months to ensure continued stability and performance. ***

1. We recommend to assemble this product with the assistance of another person. This will provide a smooth assembly process , and can help eliminate self injuries or damage to the product during assembly.
2. Please do not over tighten screws or bolt until the assembly is completed.
3. Please put all parts on a smooth , flat surface before assembly , and carefully follow the assembly steps to assemble your newly purchased correctly and efficiently.




PARTS LIST		
NO.	COMPONENT	QTY.
A	Seat 	1 pc
B	Back Leg - Left 	1 pc
C	Back Leg - Right 	1 pc
D	Front Leg - Left 	1 pc
E	Front Leg - Right 	1 pc
F	Side Stretcher 	2 pcs
G	Front & Back Stretcher 	2 pcs

HARDWARE LIST		
NO.	COMPONENT	QTY.
1	JCBC Bolt M6 x 80mm 	4 pcs
2	JCBC Bolt M6 x 60mm 	4 pcs
3	Spring Washer 	8 pcs
4	Flat Washer 	8 pcs
5	CB Screw M4 x 38mm 	8 pcs
6	Allen Wrench 	1 pc

* Phillips screwdriver not included *

Step 1




Important Note :

Ensure all bolts remain loosely tightened until final assembly adjustments are made.

Do not fully tighten from this step

Begin by removing the black woven cover from the Seat (A). Attach Back Leg - Left (CL)(B) & Back Leg - Right (CR) (C) , to the Seat (A) using 4pcs JCBC bolts (1) , 4pcs Spring Washers (3) and 4pcs Flat Washers (4) to the corner holes as shown in the diagram. Loosely tighten with Allen Wrench (6).


Step 2



Do not fully tighten from this step


Attach Front Leg - Left (CL)(D) & Front Leg - Right (CR) (E) , to the Seat (A) using 4pcs JCBC bolts (2) , 4pcs Spring Washers (3) and 4pcs Flat Washers (4). Loosely tighten with Allen Wrench (6).

Step 3



Attach the Front & Back Stretcher (G) to the Legs. Insert 4pcs CB Screws (5) using Phillips screwdriver (not provided) to drive and tighten them securely.

Step 4



Attach the Side Stretcher (F) to the front & back legs. Insert 4pcs CB Screws (5) using Phillips screwdriver (not provided) to drive and tighten them securely.

Step 5

Final Adjustment Step :

1. Place the barstool on a flat, level surface.
2. Check that all legs make even contact with the floor. If uneven, adjust the Seat (A) by tilting as needed.
3. Once level, securely tighten all bolts.
4. Attach the black woven to the Seat (A). (As shown in diagram)

