Foster Ovens

Milano 30" double Stainless Steel - 7169 900

HIGHLIGHTS



XXL Chamber capacity

The Milano Ovens, have a considerable chamber capacity, with six levels of cooking. A valuable practicality for all types of cooking.



Three lights, placed asymmetrically, provide perfect lighting, whatever cooking level is chosen.



The practicality and accessibility to the cooking chamber are increased with the exclusive supply of full extension telescopic chromed



Easy cleaning

The Foster Milano oven is supplied with a special antifingerprint treatment that makes cleaning the outside of the oven simple and quick.

FOSTER MILANO INC. 6001 NORTH POWERLINE ROAD FORT LAUDERDALE, FLORIDA 33309 info@foster-us.com www.foster-us.com

S Dual ventilation

The dual fans provides perfect heat distribution inside the chamber, with surprisingly good results even for the more challenging recipes.

Pyrolitic cleaning

Pyrolysis is the easiest way to guarantee an oven that is always clean. Once the cleaning cycle is terminated, just use a damp cloth to remove the residue.



Meat Probe

Experience the precision of professional cooking with our meat probe that measure in real time, the core temperature of your food.



Perfect safety

The ability to lock the oven door and the keyboard along with the four glass doors supplied with the oven are the best guarantees for safe and serene use.



COOKING FUNCTIONS





Foster Ovens

Milano 30" double Stainless Steel - 7169 900

Model	Milano 30" double SS
Oven Type	Multifunction Pyrolitic Double Oven
Door finishing	Satin finish Stainless Steel
cooking Functions	13
Control Type	Electronic
Temperature control	Electronic
Commands	4 knobs / 6 touch keys
Language	English
Special features	
Cleaning function	Pyrolitic self clean
Probe T control	yes
Preset/last uesd temperature memory	yes
Preheat bar (25%, 50%, 75%, 100%)	yes
Automatic fast preheat	yes
Sabbath mode	Yes
Safety	Keyboard lock, Child door lock
Temperature unit	°C/°F
Clock format	12/24 Hours
Cooking Functions	Pyrolitic Sel Clean with automatic door lock; Dual convection Bake; convection Broil; Convection Roast; Lower Convection (Pizza function); Bake; Broil; Delicate cooking; Defrost; Proof warm; Keep warm (warm plus); Light; Fast preheating.
Cavity	
Usable capacity	4,1CuFt
cavity finish	Dark gray pyrolitic enamel
Rack positions	<u>6</u>
Lighting	Triple asimmetrical halogen (20W) lighting
Broil upper heating element	3500 W (240 V)
Upper aux element	1032 W (240 V)

3000 W (240 V)

Full glass

2 x 1300 W (240 V)

4 heat resistant glasses

Heavy duty Steady Tilt

Satin finish Stainless steel handle

Concealed bake lower heating

Convection element

element

Door

door Glasses

Inner side

hinges

Handle

Technical Specifications	
Electric supply	120/240VAC - 60Hz // 120/208VAC - 60Hz
Max Amp usage, power rating (240V,60Hz)	33.8 - 7.68kW
Max Amp usage, power rating (208V,60Hz)	32.4 - 6.48kW
cable + conduit	yes
certification	USA & CA (ETL)
Warranty	24 months
Delivered accessories	
Chromed racks	2 per cavity
telescopic chromed rack	1 per cavity
Enamelled grill set	1 per cavity
Meat Probe	1



