

PWM 908 [EL DP NAM]

Professional washing machine, electrically heated, with drain pump with short runtimes and programs specific to the target group.



- Drum volume 2.58 (73)Cubic ft, load capacity 18 (8.0)US pound
- Tested for intensive use – unique Miele quality
- Top convenience with full-touch color display – M Touch Flex
- Thorough cleaning with professional washing programs
- Future-proof networking via WiFi

EAN: 4002516229070 / material number: 11204470

Model and design	
Design	Front-loader, stackable
Product line	Performance Plus
Front	Stainless steel
Load in lbs (kg)	18 (8.0)
Drum volume in cubic feet (l)	2.58 (73)
Door opening [Ø] in inches (mm)	11 7/8 (300)
Door opening angle in degrees	167
Door hinging	right
Maintenance-free synchronous motor	•
Honeycomb drum with perforated rear wall	•
Application	
Suitable for retirement and care homes	•
Suitable for the hotel and catering industry	•
Suitable for laundrettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas and fitness centers	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemical industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks and holiday complexes	•
Suitable for public/community care facilities	•
Performance data	
Spin speed in rpm	1,500
g factor	613
Tested operating hours	30,000
Controls	
Control system	M Touch Flex
Programmability	programmable
Max. delay start in h	96
Countdown indicator	•
Program sequence indicator	•
Language can be selected easily at any time	•
Dispensing	
Detergent dispenser drawer	3 compartments
CapDosing	•
Flexible dispensing adapter (optional)	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•

PWM 908 [EL DP NAM]

Professional washing machine, electrically heated, with drain pump with short runtimes and programs specific to the target group.



Standard electrical connection	
Type of heating	Electrical
Electrical connection	2~208-240V 60HZ
Heater rating in kW	3,80-5,00
Total connected load in kW	4,00-5,20
Fuse rating in A	30
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Drain pump	DN 22
Dimensions and weight	
External dimensions, net height in inches	33 1/2 (850)
External dimensions, net width in inches	23 7/8 (605)
External dimensions, net depth in inches	28 1/8 (714)
External dimensions, gross height in inches	37 1/8 (940)
External dimensions, gross width in inches	660
External dimensions, gross depth in inches	30 1/4 (768)
Net weight in lbs.(kg)	230 (104)
Gross weight in lbs.	239 (108)
Maximum floor loading in Mj/h	2820
Emission levels	
Emissions - sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in BTU/h	1.00
Features	
3-dimensional imbalance monitoring	•
Commercial shock absorber	•
Hard-wearing stainless-steel flange	•
Disinfection rinse	•
EcoSpeed	•
SoftSteam	•
Efficient rib technology	•
Temperature monitoring	•
Special heater element	•
Automatic load control	•
Volumetric flow meter	•
LED drum lighting, class 1	•
Communication slot	•
Adding laundry	•
Appliance-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Test certificates and symbols	
WEEE	•
c ETL US	•