


RADS-61R
6,000 BTUH
Nominal

FEATURES

- Electronic controls with full feature remote
- Adjustable air direction
- Easy-access, slide-out, washable filter
- One degree temperature adjustment
- 24-hour on/off timer and auto restart, energy saver function; auto, dehumidification and sleep modes
- Smartphone Compatible


SPECIFICATIONS

Cooling Capacity BTUH	6,000
Approx. Sq. Ft. Cooling	150-250
EER/CEER	12.2/12.1
Heating Capacity BTUH (electric)	N/A
Power Supply	115V 60Hz
Humidity Removal Pts/Hr	1.48
Ventilation Control	No
Fan Only	Yes
Fan Speeds Cool/Fan	3/3
Air Delivery Max. CFM	169
dB Level (hi/med/low)	56/53/52
Amps Cooling	3.7
Amps Heating	N/A
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Slide-Out Chassis	No
Window Mounting Kit	Yes
Remote Control	Yes
Refrigerant Type	R32
Shipping Weight (lbs.)	48.5
Dimensions (in.)	Height 13.4
	Width 18.5
	Depth 15.7


RADS-81R01
8,000 BTUH
Nominal

FEATURES

- Electronic controls with full feature remote and auto restart
- Four-way adjustable air direction
- Easy-access, slide-out, washable filter
- One degree temperature adjustment
- 24-hour on/off timer and auto restart, energy saver function; auto, dehumidification and sleep modes
- Smartphone Compatible


SPECIFICATIONS

Cooling Capacity BTUH	8,000
Approx. Sq. Ft. Cooling	300-350
EER/CEER	3.34/11.4
Heating Capacity BTUH (electric)	N/A
Power Supply	115V 60Hz
Humidity Removal Pts/Hr	2.11
Ventilation Control	No
Fan Only	Yes
Fan Speeds Cool/Fan	3/3
Air Delivery Max. CFM	188
dB Level (hi/med/low)	61/58/55
Amps Cooling	6.27
Amps Heating	N/A
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Slide-Out Chassis	No
Window Mounting Kit	Yes
Remote Control	Yes
Refrigerant Type	R32
Shipping Weight (lbs.)	53.26
Dimensions (in.)	Height 13.4
	Width 18.5
	Depth 15.7


RADS-101R01
10,000 BTUH
Nominal

FEATURES

- Electronic controls with full feature remote and auto restart
- Four-way adjustable air direction
- Easy-access, slide-out, washable filter
- One degree temperature adjustment
- 24-hour on/off timer and auto restart, energy saver function; auto, dehumidification and sleep modes
- Smartphone Compatible


SPECIFICATIONS

Cooling Capacity BTUH	10,000
Approx. Sq. Ft. Cooling	400-450
EER/CEER	3.34/11.4
Heating Capacity BTUH (electric)	N/A
Power Supply	115V 60Hz
Humidity Removal Pts/Hr	2.32
Ventilation Control	Yes
Fan Only	Yes
Fan Speeds Cool/Fan	3/3
Air Delivery Max. CFM	317
dB Level (hi/med/low)	61/57.5/54
Amps Cooling	7.8
Amps Heating	N/A
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Slide-Out Chassis	No
Window Mounting Kit	Yes
Remote Control	Yes
Refrigerant Type	R32
Shipping Weight (lbs.)	65
Dimensions (in.)	Height 14.6
	Width 21.5
	Depth 19.0