

Imagine T2



SPECIFICATIONS

FREQUENCY RANGE	
On Axis @ 0° ± 3dB	34-23,000Hz
On Axis @ 0° ± 1 1/2dB	36-20,000Hz
Off Axis @ 30° ± 1 1/2dB	36-10,000Hz
LF Cutoff -10dB	29Hz
SENSITIVITY	
Anechoic Chamber	88dB
Typical Listening Room	90dB
IMPEDANCE	
Nominal	6 Ohms
Minimum	4 Ohms
INPUT POWER	
Recommended Program	20-300 Watts
	300 Watts
ACOUSTIC DESIGN	
Tweeter	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet
Midrange	4" (102mm) Clay/Ceramic filled Polypropylene Cone Rubber Surround
Woofer	3 x 5 1/4" (133mm) Clay/Ceramic filled Polypropylene Cone Rubber Surround
Crossover	500Hz LR4, 1800Hz, LR4
Internal Volume	1.12 ft³ (31.8 litre)
Design Type	Transitional 5-way System Triple Port Bass Reflex 3 Individual Woofer Chambers Rear Port x 3
SIZE (W x H x D)	
Gross Dimensions including Grille, Feet, and Terminals	8 3/8 x 40 5/8 x 13 5/8" (210 x 1031 x 346mm)
WEIGHT	
Net	42.6lb (19.4kg)/each
Shipping	59lb (26.8kg)/each
FINISH	
	Black Ash, Dark Cherry or Walnut Wood Veneer, Gloss Black or Gloss White
FEATURES	
	Dual, 5-way Gold-plated Binding Posts Bi-wireable/Bi-ampable Feet/Stabilizers with Adjustable Spikes and Rubber Levellers Port Plug

All specifications are subject to change without notice. PSB, PSB Speakers, and Imagine are trademarks of, or used under license by, PSB Speakers, a division of Lenbrook Industries Limited.
© November 2011 PSB Speakers. 11-067 All rights reserved.

REAL SOUND for REAL PEOPLE