IWSub Reference & SubAmp 600 Specifications

IWSub Reference

 Outer Dimensions:
 $15\frac{1}{2}$ " W x $26\frac{3}{16}$ " H

 Cut-out Size:
 $14\frac{3}{8}$ " W x $25\frac{1}{8}$ " H

 Rec. Assoc. Amp:
 SubAmp 600

 Frequency Response:
 14 Hz - 200 Hz

Nominal Impedance: 4 ohms

Driver Complement:One 13" long-excursion woofer coupled to a 13" infrasonic radiator

Enclosure: Non-resonant sealed medite

enclosure

Net Weight: 26 lbs.

SubAmp 600

One Channel Operation: 275 Watts
Two Channels Driven: 230 Watts each

With Brackets, Feet removed: $3^7/16^{"}$ H x $19^1/16^{"}$ W x $9^5/8^{"}$ D Without Brackets, including Feet: $3^{11}/16^{"}$ H x $17^1/16^{"}$ W x $9^5/8^{"}$ D

When installing the SubAmp 600 in either professional audio racks or in AVrack furniture, be sure to leave adequate ventilation space around the SubAmp 600 unit. Ideally, we recommend leaving a single rack unit open above and below the product.

Visit us at www.definitivetech.com and learn about all our exciting products.