QUICK REFERENCE GUIDE > BH1-30-N

Date: 25.03.2025 > 1

# 30" Series 7 Grill, Natural Gas

Series 7

Stainless Steel | Natural Gas



Designed with flexibility in mind, DCS Grills allow you to cook a wide variety of meals and are engineered to deliver the functionality and power demanded by a professional chef. DCS Grills are hand-finished to perfection to complement the quality of the DCS premium outdoor kitchen and built to withstand the demands of the serious cook and the extremes of mother nature. Available in Natural and LP Gas.

## DIMENSIONS

Height 24 1/4 "

Width 30 "

Depth 26 5/8 "

# FEATURES & BENEFITS

#### Stainless Steel Burners

The precision ported U-shaped stainless steel burners are rated at a massive 25,000BTU each, offering premium quality and performance. A heat shield directs heat upwards maximizing heating efficiency.

#### Ceramic Radiant Technology

A layer of ceramic rods provides intense yet even heat. It gives a consistent grilling surface, with controlled heat rather than direct fire.

#### **Direct Burner Ignition**

An ergonomic ignition solution, where burners are lit directly from the corresponding knobs.

#### Temperature Gauge - Zero To Sear

Go from zero to sear with DCS Grills' new built-in temperature gauge. It lets you know exactly how hot the grill is, even when the hood is down.

### **SPECIFICATIONS**

#### Accessories (sold separately)

Built-in grill cover	ACBI-30
Insulated jacket	BGB30-IJS (optional)
On cart grill cover	ACC-30
Optional cart mount	CAD1-30 / BGB30-CSS

#### Burners

Number of U-burners

#### Cooking Surface Area

Primary cooking area	553 sq.in.
Total cooking area	748 sq.in.
Warming rack area	195 sq.in.

2

#### **Features**

Full surface searing	•
Hood temperature gauge	•
Ignition system	Spark
Metal dials	•
Warming rack	•

#### Finish

Material	304 grade
	stainless steel
Weather resistant	•

### **Gas Requirements**

1	/2" NPT male with 3/8" in flare adapter	•
(	Gas type	NG
(	Operational pressure	4" W.C.
Ş	Supply pressure	6" to 9" W.C.

#### **Installation Dimensions**



QUICK REFERENCE GUIDE > BH1-30-N

Date: 25.03.2025 > 2

Cutout depth (proud)	22 3/4 "	$\overline{ullet}$	Guide d'installation FR
Cutout height (proud)	10 1/8 "	$\underline{ullet}$	Guía de instalación SP
Cutout width (proud)	28 1/2 "	$\overline{1}$	Planning Guide EN - Professional Grills Series 7 Outdoor Kitchen
Insulated jacket for proud cut-out Varies - check manual		$\underline{\downarrow}$	Revit-18 Grill
	manuai	$\overline{\underline{\downarrow}}$	Rhino-5 Grill
		$\overline{\underline{\downarrow}}$	Rhino-5 Grill
Performance		$\overline{ullet}$	Rhino-5 Grill
		$\overline{ullet}$	Rhino-5 Grill with Insulated Jacket
Total Power	50000 BTU	$\overline{ullet}$	Rhino-5 Grill with Insulated Jacket
U-burner power 25000 BTU		<u></u>	Service and Warranty
		$\underline{ullet}$	Sketchup-8 Grill
		$\underline{ullet}$	Sketchup-8 Grill with Insulated Jacket
Power requirements		$\overline{ullet}$	User Guide Grill EN
Grill power supply	9V Battery for	$\overline{ullet}$	Guide d'utilisation FR
Offit power supply	Ignition	$\underline{ullet}$	Guía del usuario SP

SKU 71639

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

### Other product downloads available at dcsappliances.com

- ↓ 2D-DWG Grill
- 2D-DWG Grill with Insulated Jacket
- 2D-DXF Grill with Insulated Jacket

Installation Guide Grill EN

# A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com

