

UP48N



Colour range

Body



Blue grey - BG



Antique white - AW



White - WH



Blue - MB



Stainless steel - SS



Graphite matt - MG



Glossy black - BK



Burgundy red - BU



Emerald green - EG



RAL
Optional RAL - RA
+

Finishes

Knobs, handles, frames (optional)



Brass - G



Copper - P



Chrome - C



Burnished - B

Optional solid door version

optional +

Order code: add letter "Q" before the "N" letter

Noblesse frames

optional → p. 138

Available ovens

Electric oven

Primary oven:
UOV 80 M


Maximum input:
3.7 kW

Secondary oven:
UOV 30 E


Maximum input:
2.5 kW

Configurations


5 burners with fry top* and coup de feu



8 burners with fry top*



Induction



Electric oven

UP48FSNMP

Brass/Copper/Chrome/Burnished

UP48FNMP

Brass/Copper/Chrome/Burnished

UPI486NMP

Brass/Copper/Chrome/Burnished

Consumption

<p>Bridge induction zone Ø 7" 1/4 + Ø 7" 1/4 1.85 / 2.5 kW + 1.85 kW</p>	<p>Induction zone Ø 5" 3/4 1.4 / 1.8 kW</p>	<p>Induction zone Ø 7" 1/4 1.85 / 2.5 kW</p>	<p>Induction zone Ø 8" 11/16 2.3 / 3.2 kW</p>	<p>Coupe de Feu 5500 btu/h</p>	<p>Double ring Dual burner 25000 btu/h / 900 btu/h</p>
<p>Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h</p>	<p>Oval burner 10500 btu/h / 3100 btu/h</p>	<p>Big burner 10500 btu/h / 2000 btu/h</p>	<p>Small burner 7000 btu/h / 1400 btu/h</p>		

Complements & accessories

→ p. 136

Hood

UAG48

Hood

UANB48

Ladle holder panel

AM4-120

Brass/Copper/Chrome/Burnished

Technical drawing & dimensions

