

SPECIFICATIONS AX SERIES RANGE HOODS



160 CFM/6.5 Sones @ 0.10" SP. Horizontal 160 CFM/6.5 Sones @ 0.10" SP. Vertical

Dimensions

Overall bottom projection - 183/8" Overall top projection -12" Height - 6" Available widths: 30"

Hood Body

Stainless Steel: 24 gauge, grade 430 stainless steel.

Painted: 23 gauge cold rolled commercial grade (CRCQ) steel, auto welded, coated with a baked enamel finish.

Motor

2 speed, single coil, thermally protected, permanently lubricated. Rated 120 volts, $60\ hz$.

Lighting

Single 60 watt cook light capacity (bulb not included).

Ducting Options


Horizontal ducting: $3^{1/4}$ "x10" (duct adapter and damper included). Vertical ducting: $3^{1/4}$ "x10" (duct adapter and damper included).


Fan Blade

One piece polymeric, electronically balanced blade. $6^{5/8}^{\shortparallel}$ diameter with 5 paddles.

Electrical connection

Hood top - 7/8" electrical knockout. Hood back - 7/8" electrical knockout.





Filters

UL rated, class 2 filter. Grease Filter: RF35 - 87/8"x103/8" (included).

Available Finishes

White, Black & Stainless Steel.

EXPANDED PERFORMANCE										
	Static Pressure (inches of w.g.)						Sones	Fan Speed	Power	
Air Flow - CFM	0	0.05	0.1	0.15	0.2	0.25	@ .1 SP	RPM	Watts	Apms
Vertical Ducting	201	180	160	140	117	91	6.5	2680	56.0	2.1
Horizontal Ducting	201	179	160	140	117	95	6.5	2602	56.0	2.1

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN NUMBER	MODEL NUMBER	СҒМ	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	





U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785

Fax: (610) 696-8048

Canada: 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 • 800-250-8767 Fax: (905) 456-1015

Specifications subject to change without notice.