

## Description

The Profile™ Pr44 Series is the ideal solution for small home theater systems and everyday TV viewing. These slim cabinets are equipped with dual high-fidelity 4" drivers and 1" cloth-dome tweeters to provide excellent sonic clarity at all volumes. With versatile mounting options and precision craftsmanship, the Profile Pr44 Series is the perfect complement to 50" - 60" TVs in small to medium-sized rooms.

## **Key Features**

- Custom crafted to match the exact height and finish of any display
- As thin as 2.25" deep to ensure compatibility with flat-screen TVs
- Easily mounts to articulating TVs or to the wall with Leon's brackets
- Available as a stereo pair or multichannel speakers
- Solid MDF construction, handcrafted in the USA

Recommended Pairings: Axis AxV60, Detail Ds44UX, Aaros A10-UT



|   | Pr44                                  | Pr44UX                                       |
|---|---------------------------------------|--|
| HEIGHT  | Exact height of TV                    | Exact height of TV                           |
| WIDTH   | 6"                                    | 6"   |
| DEPTH   | 3.25" (3.5" with grill)               | 2.25" (2.5" with grill)                      |
| MATERIAL  | MDF Enclosure                         | MDF enclosure                                |
| WEIGHT  | 20-35 lbs.                            | 15-30 lbs.                                   |
| FINISH  | Match TV color (or any custom finish) | Match TV color (or any custom finish)        |
| GRILL   | Standard woven fabric                 | Standard woven fabric                        |
| CONNECTIONS   | Spring-loaded terminals               | Spring-loaded terminals                      |
| COMPONENTS  | 4" woofers; 1" tweeters               | 4" ultra-thin woofers; 1" silk-dome tweeters |
| IMPEDANCE   | L/R: 8Ω; -MC: 4Ω                      | L/R:6Ω; -MC:4Ω                               |
| REC. POWER  | L/R: 50-200W                          | L/R: 25-125W                                 |
| MAX. OUTPUT   | L/R: 100dB avg; 105dB peak            | L/R: 100dB avg; 104 dB peak                  |
| COVERAGE  | L/R: Hor: 140°; Vert: 110°            | L/R: Hor: 140°; Vert: 110°                   |
| FREQ. RESP.   | L/R: 95–20kHz                         | L/R: 110–20kHz                               |
| SENSITIVITY   | L/R: 87dB@2.83V/1m                    | L/R: 88dB @ 2.83V/1m                         |
| CONFIGURATIONS  | Pr44, Pr44-MC                         | Pr44UX, Pr44UX-MC                            |
| MOUNTING BRACKETS Works with: PrSMB, PrMMB, FLSH, PrTTS |                                       |  |

## COMPARE MODELS

