

Specs & Details

Dimensions: 16 H x 42 W x 20 13/16 D

ACCESSORIES

Accessories Required for Installation	RAB42 - Wall Case Outdoor Grille
---------------------------------------	-------------------------------------

APPEARANCE

Color Appearance	Grey White
------------------	------------

CAPACITY

CFM Indoor Fan High	495
CFM Indoor Fan Low	330
Cooling BTUH (MAX)	15100
Cooling BTUH (MIN)	14,700 Btu
Cooling EER (BTUH / Watt)	10.4 / 10.4
Dehumidification (pts./hr.)	4.1 (High Speed)
Vent CFM (high fan at zero ESP)	47.5

FEATURES

Central Desk Control Compatibility	Yes
Chassis Type	Slide-In
Control Type	Standard Microcomputer Tactile touch pad with LED Display
Corrosion Treated	Yes
Discharge Grille	2-position
Electronic Micro Computer Control	Yes
Fan Cycle Switch	Yes
Fan Motor	2
Fan Speed Control	Yes

Fan Speed Selections	Hi/Low Cooling Hi/Low Heating Hi/Low Fan Only
Filter Type	Rigid Frame Slide-Out
Freeze Sentinel	Yes
Heat - Cool	Yes
Heat Pump	Yes
Heat Sentinel	Yes
Heating - Reverse Cycle - COP	3.4/3.5
Heating System	Heat Pump With Backup Resistance Heat
Internal Condensate Removal (ICR)	Yes
Louver Style	Reversible
Manual Vent Control	Hidden
Power Factor	95
Product Type	Packaged Terminal Air Conditioners (PTAC)
Refrigerant Charge (oz.)	34
Refrigerant Type	R454B
Rotary Compressor	Yes
Sensible Heat Ratio	0.75
Temperature Limiting	Electronic 24-Step
Temperature Range	60 - 85 F
Vent Control	3-position
Venting Features	Concealed Manual Vent Control Vent Air Filter Outdoor Vent Control - 3 Positions
Zoneline Features	"Smart Fan" Fan Cycle Control Heat Sentinel Freeze Sentinel Automatic Indoor Frost Control Universal Heaters Auto Power Recovery Remote Thermostat Compatibility Central Desk Control Compatibility Random Twist/Length Segment Tangential Blower

POWER / RATINGS

Cooling - Amperes	6.7/7.1
Cooling - Amperes; F.L. - Cooling	6.1/6.6
Cooling - Amperes; L.R.	31.5
Cooling - Watts	1450/1410
Heating BTUH	14000 / 13800
Heating - Electric - Heater Amps	5.6/6.0
Heating - Reverse Cycle - Watts	1235/1225
Voltage (MAX)	230 V
Voltage (MIN)	208 V

WARRANTY

Labor Warranty	Limited 1-year entire appliance Limited 5-year sealed system
Parts Warranty	Limited 2-year entire appliance
Warranty Notes	See written warranty for full details

WEIGHTS & DIMENSIONS

Approximate Shipping Weight	120 lb
Net Weight	110 lb
Overall Depth	20 13/16 in
Overall Height	16 in
Overall Width	42 in