## **GAS INSERTS**



# IRONSTRIKE GAS INSERTS MADISON PARK<sup>TM</sup>



The Madison Park gas fireplace insert brings convenience and efficient heating to an existing wood-burning fireplace. Listed to fit zero-clearance factory-built and masonry fireplaces, the Madison Park gas insert turns your standard wood burning fireplace into a cost-effective heat source that displays a realistic gas fire for brilliant warmth and ambiance.

#### **OVERVIEW**

- Available in large, medium and small models to fit a wide range of fireplace sizes.
- ♦ Electronic ignition system with battery backup—still ignites and heats during a power outage.
- Outstanding heating efficiency for increased comfort and lower operating costs.
- Ceramic glass for optimum heat transfer and a protective screen\*.
- Beautifully crafted high-definition ceramic fiber log set.
- State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- Ochoose between several distinctive styles of accessory façades to match the look of your existing décor (required).
- Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).
- Mood enhancing interior illumination with six distinctive settings (large & medium models).
- Factory installed blower with six speed settings to fine tune your heating needs.
- Full-function remote control included (IPI/CPI, thermostat, flame height, blower, lighting).
- ♦ 20 year limited warranty.

<sup>\*</sup>All applicable models comply with ANSI Z21.50/88 barrier requirements.



Madison Park 27 shown with Full Face façade and Heritage Brown liner.

## **MADISON PARK 34**

BTU INPUT NG: 25,000 - 38,000 BTU INPUT LP: 27,000 - 35,500

**HEATING CAPACITY:** 500 – 2000 square feet AFUE EFFICIENCY: 67% (NG) 73% (LP

ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP)

**BLOWER: 150-CFM** 

**REMOTE CONTROL: Standard** 

## **MADISON PARK 32**

BTU INPUT NG: 23,000 - 34,000 BTU INPUT LP: 28,000 - 34,000

**HEATING CAPACITY:** 500 – 1,750 square feet

AFUE EFFICIENCY: 71% (NG) 74% (LP

ENERGUIDE (P4) EFFICIENCY: 65% (NG) 70% (LP)

**BLOWER: 150-CFM** 

**REMOTE CONTROL: Standard** 

## **MADISON PARK 27**

BTU INPUT NG: 18,000 - 25,000 BTU INPUT LP: 16,000 - 22,500

**HEATING CAPACITY:** 450 – 1,625 square feet AFUE EFFICIENCY: 78% (NG) 75% (LP

ENERGUIDE (P4) EFFICIENCY: 73% (NG) 73% (LP)

**BLOWER: 150-CFM** 

**REMOTE CONTROL: Standard** 

### **OPTIONS**

#### **FACADES**

Choose a face style that's right for your home.



Full Face Facade



Contemporary



Decco

#### **DECORATIVE ACCENT TRIMS**

(For use with Full Face Façade only)



Frontier



Highliner



Iron Rail

#### LINER



Black Tie



Heritage Brown



Porcelain



Flat Black

#### **REMOTE**



The stardard Total Comfort Remote uses an intergrated thermostat to keep your room at just the right temperature.



The Madison Park CD gas fireplace insert adds the convenience of gas with contemporary styling to an existing wood burning fireplace. Listed to fit small zero-clearance factory-built and masonry fireplaces, the Madison Park CD turns your standard wood burning fireplace into a stylish and convenient heat source that you control with the press of a button.

#### **OVERVIEW**

- Available in large, medium and small models to fit a wide range of fireplace sizes.
- ♦ Electronic ignition system with battery backup—still ignites and heats during a power outage.
- Outstanding heating efficiency for increased comfort and lower operating costs.
- Oceramic glass for optimum heat transfer and a protective screen\*.
- ♦ State-of-the-art burn technology and glass floor media provide a stunning flame presentation.
- Ohoose between several distinctive styles of accessory façades to match the look of your existing décor (required).
- Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).
- Reflective black crushed glass media included with several optional colors available to customize the look
- ♦ Mood enhancing interior illumination with six distinctive settings (large & medium models).
- Factory installed blower with six speed settings to fine tune your heating needs.
- Full-function remote control included (IPI/CPI, thermostat, flame height, blower, lighting).
- 20 year limited warranty.

<sup>\*</sup>All applicable models comply with ANSI Z21.50/88 barrier requirements.



Madison Park CD shown with Contemporary Facade and Porcelain Liner.

## **MADISON PARK CD 34**

BTU INPUT NG: 25,000 - 38,000 BTU INPUT LP: 27,000 - 35,500

**HEATING CAPACITY:** 500 – 2000 square feet AFUE EFFICIENCY: 68% (NG) 70% (LP

ENERGUIDE (P4) EFFICIENCY: 66% (NG) 70% (LP)

**BLOWER: 150-CFM** 

**REMOTE CONTROL: Standard** 

## **MADISON PARK CD 32**

BTU INPUT NG: 23,000 - 34,000 BTU INPUT LP: 28,000 - 34,000

**HEATING CAPACITY:** 500 – 1,750 square feet

AFUE EFFICIENCY: 72% (NG) 74% (LP)

ENERGUIDE (P4) EFFICIENCY: 67% (NG) 72% (LP)

**BLOWER: 150-CFM** 

**REMOTE CONTROL: Standard** 

## **MADISON PARK CD 27**

BTU INPUT NG: 21,000 - 30,000 BTU INPUT LP: 20,000 - 25,000

**HEATING CAPACITY:** 500 – 1,500 square feet AFUE EFFICIENCY: 67% (NG) 69% (LP)

ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP)

**BLOWER: 150-CFM** 

**REMOTE CONTROL: Standard** 

### **OPTIONS**

#### **FACADES**

Choose a face style that's right for your home.



Full Face Façade



Contemporary



Deco

#### **DECORATIVE ACCENT TRIMS**

(For use with Full Face Façade only)



Frontier



Highliner



Iron Rail

#### LINER



Black Tie

Porcelain



Heritage Brown



Flat Black



Reflective Black (Std)



Platinum



Reflective Blue

#### **REMOTE**



The stardard Total Comfort Remote uses an intergrated thermostat to keep your room at just the right temperature.

## IRONSTRIKE GAS INSERTS RAVENNA TM



The Ravenna gas fireplace insert offers the convenience of gas, the look of a real wood fire and an efficient source of supplemental heat. Listed to fit most zero-clearance factory-built and masonry fireplaces, the Ravenna turns your standard fireplace into a cost-effective heat source and warm, beautiful gathering place.

#### **OVERVIEW**

- Available in a medium size to fit most common fireplace sizes.
- Electronic ignition models include a battery backup—still ignites and heats during a power outage.
- Outstanding heating efficiency for increased comfort and lower operating costs.
- Ceramic glass for optimum heat transfer and a protective screen\*.
- Beautifully crafted high-definition ceramic fiber log set.
- State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- Interior selection consists of a natural tan brick ceramic fiber liner (required).
- Factory installed blower with six speed settings to fine tune your heating needs.
- ♦ Full-function remote control included (IPI/CPI, thermostat, flame height, blower).
- 20 year limited warranty.

<sup>\*</sup>All applicable models comply with ANSI Z21.50/88 barrier requirements.



Ravenna 40 shown with Contemporary face and Tan Brick liner.

## **RAVENNA 40**

BTU INPUT NG: 28,000 - 40,000 BTU INPUT LP: 26,000 - 37,500

**HEATING CAPACITY:** 500 – 2000 square feet

ENERGUIDE (P4) EFFICIENCY: 67% (NG) 69% (LP)

**BLOWER:** 150-CFM

**REMOTE CONTROL:** Standard

## **RAVENNA 33**

BTU INPUT NG: 24,000 - 33,000 BTU INPUT LP: 24,000 - 33,000

**HEATING CAPACITY:** 500 – 2000 square feet

ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP)

**BLOWER:** 150-CFM

**REMOTE CONTROL: Standard** 

## **OPTIONS**

#### **FACE STYLE & FINISH**



Contemporary

Black

#### LINER



Tan Brick

#### SURROUND AND TRIM

Choose your surround and trim.




Standard surround



#### **REMOTE**



The stardard Total Comfort Remote uses an intergrated thermostat to keep your room at just the right temperature.



		Madison Park 27	Madison Park CD 27	Madison Park 32	Madison Park CD 32	Madison Park 34	Madison Park CD 34	Ravenna 33/40
Width	Front	26-5/8"	26-5/8"	31-5/8"	31-5/8"	33-5/8"	33-5/8"	31-1/4"
	Back/Rear	16-3/4"	16-3/4"	21"	21"	23"	23"	17-5/8"
Height	Overall	17-7/8	17-7/8"	19-3/8"	19-3/8"	23-7/8"	23-7/8"	19-3/8"
Depth	Overall	14-7/8"	14-7/8"	15-7/8"	15-7/8"	16-1/4"	16-1/4"	15-7/8"
To Centerl 3" Flue Co	ine (CL) of ollar	8-3/16"	8-3/16"	9-3/4"	9-3/4"	10"	10"	13-3/8"

#### MINIMUM CLEARANCES TO COMBUSTIBLES

Hearth protection to be minimum of 3/8" thick non-combustible or equivalent, with a k factor of .84.

		Madison Park 27 &	Madison Park 32 &	Madison Park 34 & Madison Park CD 34	Ravenna 33	Ravenna 40	
		Madison Park CD 27	Madison Park CD 27 Madison Park CD 32				
A	1-1/2" Top facing to bottom of appliance	32"	32"	36"	31-1/2"	35-1/2"	
E	Side facing or side wall to center of glass	23"	25-7/8"	26-7/8"	25-1/2"	25-1/2"	
(	6" Mantel to bottom of appliance	34"	32"	36"	39"	43"	
[	Vertical distance from base of appliance to hearth extension	0" 4"	0" 10"	0" 10"	0" 2" 4"	0" 2" 4"	
E	Minimum horizontal distance from front of appliance	10" 0"	2" 0"	2" 0"	13" 10" 0"	14" 10" 0"	

	Madison Park™ 27 &	Madison Park™ 32 &	Madison Park™ 34 &	Ravenna™ 33/40
	Madison Park™ CD 27	Madison Park™ CD 32	Madison Park™ CD 34	Naveilla 33/40
	26" H X 37" W	26" H X 41" W	31" H X 41" W	29" H X 41" W
Standard Surround	26" H X 41" W	26" H X 46" W	31" H X 46" W	29" H X 48" W
3-pc	30" H X 37" W	33" H X 41" W	34" H X 41" W	33" H X 41" W
	30" H X 41" W	33" H X 46" W	34" H X 46" W	33" H X 48" W
Standard Surround 1-pc	N/A	N/A	N/A	29" H X 41" W
4 Sided - Able to be Trimmed	38" H X 46" W	38" H X 46" W	42" H X 46" W	N/A
Cast Surround	N/A	N/A	N/A	30" H X 45-1/2" W

	Madison Park™ 27 & Madison Park™ CD 27	Madison Park™ 32 & Madison Park™ CD 32	Madison Park™ 34 & Madison Park™ CD 34	Ravenna™ 33/40
Front Width	27"	32"	34"	31-1/2"
Height	18"	19-1/2"	24"	19-1/2"
Rear Width	17"	22"	24"	18"
Depth	15"	16"	16"	16"





