RP-8203F
FLOORSTANDING LOUDSPEAKER



LEGENDARY AMERICAN SOUND SINCE 1946
Klipsch Reference Premiere Series III is designed and engineered in the USA, where Klipsch has been crafting highly efficient, premium loudspeakers for over 80 years. Reference Premiere delivers immersive, high-resolution audio – powerful and precise sound for all your movies, music, and gaming.

ADVANCED ACOUSTICS
A two-way loudspeaker design, Klipsch Reference Series III features a new high-density axial Tractrix® horn-loaded tweeter with upgraded BMC material to reduce resonance, flush-mounted to the cabinet to minimize wave breakup and measurably improve off-axis response for a wider sweet spot. Reference Premiere copper-hued Cerametallic™ woofers provide impactful and enveloping bass, and the entire series is Dolby Atmos compatible for room-filling surround sound.

PREMIUM DESIGN
Sporting a knife edge cabinet for exceptional structural integrity, Klipsch Reference Premiere speakers feature clean lines and a sleek finish – complete with a flush-mount horn tweeter. Metal outrigger feet create increased stability and allow precise angle adjustment. Iconic copper details, a floating fabric grille, and an updated input panel complete the exceptional styling.

DEPTH CHARGE
Need to go lower? You can easily add a Klipsch Reference Premiere subwoofer to your system to further enhance the home theater experience – dropping the bass to the bottom! Choose from Reference Premiere Compact Subwoofers for a smaller footprint or go even deeper with Reference Premiere Ported Subs, both with the same legendary Reference Premiere aesthetics.

SPECIFICATIONS	
FREQUENCY RESPONSE	35-25kHz +/- 3dB
SENSITIVITY	98dB @ 2.83V / 1m*
POWER HANDLING (CONT/PEAK)	150W / 600W
IMPEDANCE	8 ohm (3.46 min. @162Hz)
CROSSOVER FREQUENCY	1630Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Flush Mount BMC Axial Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 8" Cerametallic Cone Woofers with Faraday rings
ENCLOSURE MATERIAL	MDF (Internally Braced)
ENCLOSURE TYPE	Bass Reflex via dual chamber rear-firing Tractrix® Ports
INPUTS	Dual aluminum binding posts / bi-wire / bi-amp
HEIGHT	43.10" (109.5 cm)
WIDTH	10.84" (27.5 cm)
DEPTH	18.25" (46.3 cm)
WEIGHT	67.9 lbs (30.8 kg)
FINISH	Ebony, Walnut

*SPL at 1M, half-space anechoic with 2.83V input, in-room sensitivity

FINISH TYPE	SKU	UPC	EAN
EBONY	1080629	743878093704	0743878093704
WALNUT	1080632	743878093711	0743878093711

All specifications are subject to change without notice. ©2026 Premium Audio Company, LLC, a wholly owned subsidiary of Gentex Corporation (NASDAQ: GNTX). Klipsch is a trademark registered in the USA and other countries, and is owned by Klipsch Group, Inc.