

Amplifier Type	Class D	
CEA-2006 Primary Ratings	Power Output	45Watts RMS x 4 at 4 Ohms, $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	82dBa (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	400W
RMS Power at 14.4V	A/B (2 Ohms)	45Watts RMS x 4 at 4 Ohms, 1kHz, $\leq 1\%$ THD+N
	A/B (Bridged 4Ohms)	90Watts RMS x 2 at 4 Ohms, 1kHz, $\leq 1\%$ THD+N
Specifications	Signal to Noise Ratio	98dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-20kHz (+0dB, -1dB)
	Input Impedance	10k ohm
	Speaker Impedance	4 Ω (2 Ω to 8 Ω allowable)
	Bridged Connection	4 Ω to 8 Ω allowable
Audio Section	Low-pass Filter	50-200Hz, -12dB/oct (A/B CH)
	High-pass Filter	50-200Hz, -12dB/oct (A/B CH)
	RCA Input Sensitivity	0.2 (V) - 5.0 (V)
	Speaker Level Input Sensitivity	4.0 (V) - 12.0 (V)
Terminal	Connector with DC Cable	Yes
	RCA	A/B
General	Dimensions(WxHxD)	145[mm] x 45 [mm] x 99 [mm]
		5-11/16 inch x 1-3/4 inch x 3-7/8 inch
	Weight (kg)	0.7 [kg] 1.5 [lbs]
	Operating Voltage	14.4V (11-16V allowable) [V]
	Current Consumption	15 [A]
	CTA-2006 Compliant	

Amplifier Type	Class D	
CEA-2006 Primary Ratings	Power Output	45Watts RMS x 4 at 4 Ohms, $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	82dBa (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	400W
RMS Power at 14.4V	A/B (2 Ohms)	45Watts RMS x 4 at 4 Ohms, 1kHz, $\leq 1\%$ THD+N
	A/B (Bridged 40hms)	90Watts RMS x 2 at 4 Ohms, 1kHz, $\leq 1\%$ THD+N
Specifications	Signal to Noise Ratio	98dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-20kHz (+0dB, -1dB)
	Input Impedance	10k ohm
	Speaker Impedance	4 Ω (2 Ω to 8 Ω allowable)
	Bridged Connection	4 Ω to 8 Ω allowable
Audio Section	Low-pass Filter	50-200Hz, -12dB/oct (A/B CH)
	High-pass Filter	50-200Hz, -12dB/oct (A/B CH)
	RCA Input Sensitivity	0.2 (V) - 5.0 (V)
	Speaker Level Input Sensitivity	4.0 (V) - 12.0 (V)
Terminal	Connector with DC Cable	Yes
	RCA	A/B
General	Dimensions(WxHxD)	145[mm] x 45 [mm] x 99 [mm]
		5-11/16 inch x 1-3/4 inch x 3-7/8 inch
	Weight (kg)	0.7 [kg] 1.5 [lbs]
	Operating Voltage	14.4V (11-16V allowable) [V]
	Current Consumption	15 [A]
	CTA-2006 Compliant	

Amplifier Type	Class D	
CEA-2006 Primary Ratings	Power Output	45Watts RMS x 4 at 4 Ohms, $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	82dBa (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	400W
RMS Power at 14.4V	A/B (2 Ohms)	45Watts RMS x 4 at 4 Ohms, 1kHz, $\leq 1\%$ THD+N
	A/B (Bridged 4Ohms)	90Watts RMS x 2 at 4 Ohms, 1kHz, $\leq 1\%$ THD+N
Specifications	Signal to Noise Ratio	98dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-20kHz (+0dB, -1dB)
	Input Impedance	10k ohm
	Speaker Impedance	4 Ω (2 Ω to 8 Ω allowable)
	Bridged Connection	4 Ω to 8 Ω allowable
Audio Section	Low-pass Filter	50-200Hz, -12dB/oct (A/B CH)
	High-pass Filter	50-200Hz, -12dB/oct (A/B CH)
	RCA Input Sensitivity	0.2 (V) - 5.0 (V)
	Speaker Level Input Sensitivity	4.0 (V) - 12.0 (V)
Terminal	Connector with DC Cable	Yes
	RCA	A/B
General	Dimensions(WxHxD)	145[mm] x 45 [mm] x 99 [mm]
		5-11/16 inch x 1-3/4 inch x 3-7/8 inch
	Weight (kg)	0.7 [kg] 1.5 [lbs]
	Operating Voltage	14.4V (11-16V allowable) [V]
	Current Consumption	15 [A]
	CTA-2006 Compliant	

Amplifier Type	Class D	
CEA-2006 Primary Ratings	Power Output	45Watts RMS x 4 at 4 Ohms, $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	82dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	400W
RMS Power at 14.4V	A/B (2 Ohms)	45Watts RMS x 4 at 4 Ohms, 1kHz, $\leq 1\%$ THD+N
	A/B (Bridged 4Ohms)	90Watts RMS x 2 at 4 Ohms, 1kHz, $\leq 1\%$ THD+N
Specifications	Signal to Noise Ratio	98dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-20kHz (+0dB, -1dB)
	Input Impedance	10k ohm
	Speaker Impedance	4 Ω (2 Ω to 8 Ω allowable)
	Bridged Connection	4 Ω to 8 Ω allowable
Audio Section	Low-pass Filter	50-200Hz, -12dB/oct (A/B CH)
	High-pass Filter	50-200Hz, -12dB/oct (A/B CH)
	RCA Input Sensitivity	0.2 (V) - 5.0 (V)
	Speaker Level Input Sensitivity	4.0 (V) - 12.0 (V)
Terminal	Connector with DC Cable	Yes
	RCA	A/B
General	Dimensions(WxHxD)	145[mm] x 45 [mm] x 99 [mm]
		5-11/16 inch x 1-3/4 inch x 3-7/8 inch
	Weight (kg)	0.7 [kg] 1.5 [lbs]
	Operating Voltage	14.4V (11-16V allowable) [V]
	Current Consumption	15 [A]
	CTA-2006 Compliant	