

SPECIFICATIONS

INPUTS

Audio Inputs: 7 HDMI, 6 RCA Phono, 4 Coax SPDIF, 2 Toslink
Nominal sensitivity: 1V, 2V, 4V (user selectable)
Input Impedance: 47 k Ω
Signal to Noise (A-wtd ref 100W) normal/stereo direct: 100 dB/110 dB
Frequency Response: 20 Hz – 20 kHz \pm 0.2 dB
Video Inputs: 7 HDMI (HDMI 2.0b / HDCP 2.2)

OUTPUTS

Amplifier Channels: 7
Continuous power output, per channel, 8 Ω / 4 Ω : 120W/200W
Minimum Speaker Load: 4 Ω
Preamp Audio Outputs: 16 channels (unbalanced RCA), 2 channels Zone 2 (unbalanced RCA), 1 Toslink
Nominal output level: 1 Vrms (max. 5 Vrms)
Output impedance: 560 Ω
THD+N (20 Hz – 20 kHz): -100dB
Main Video Outputs: Dual (2) HDMI (eARC support)
Second Zone Output: 1 HDMI
Headphone Output: 1 1/4"

CONTROL

IP Ethernet
Wifi
RS232 Serial Control
12 Volt Trigger Outputs: 2
IR Receiver Inputs: 2

GENERAL

Power consumption (standby): <0.5W
Power consumption (idle, typical): 90W (340 BTU/hour)
Power consumption (maximum): 1500W (5200 BTU/hour)

WEIGHTS & DIMENSIONS

Dimensions (including terminals and feet): 17"W x 17.5"D x 7.3"H (4U)
Weight: 40.3 lbs. (18.3 kg)

IN THE BOX: Concert XR-8, HTR-3 remote with 2 x AAA batteries, DAB/FM antenna, 3 x WiFi/Bluetooth antennas, calibration microphone, USB cable, power cord, user manual, warranty