

Monitor Section	Picture size	6.75 inches(diagonal) wide
	W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
DVD Section	D/A Converter	24 / 32Bit
	Audio Decoder	Linear PCM
		Dolby Audio
		MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV
	Wow & Flutter	Below Measurable Limit
	Frequency response 96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	90.5dB (DVD-Video 96k)
	Dynamic range	89dB (DVD-Video 96k)
	DISC Format	DVD-Video / VIDEO-CD / CD-DA
	Quantifying bit number	16 / 20 / 24bit
	USB Standard	USB2.0 High Speed

Monitor Section	Picture size	6.75 inches(diagonal) wide
	W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
DVD Section	D/A Converter	24 / 32Bit
	Audio Decoder	Linear PCM
		Dolby Audio
		MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV
	Wow & Flutter	Below Measurable Limit
	Frequency response 96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	90.5dB (DVD-Video 96k)
	Dynamic range	89dB (DVD-Video 96k)
	DISC Format	DVD-Video / VIDEO-CD / CD-DA
	Quantifying bit number	16 / 20 / 24bit
	USB Standard	USB2.0 High Speed

Monitor Section	Picture size	6.75 inches(diagonal) wide
	W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
DVD Section	D/A Converter	24 / 32Bit
	Audio Decoder	Linear PCM
		Dolby Audio
		MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV
	Wow & Flutter	Below Measurable Limit
	Frequency response 96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	90.5dB (DVD-Video 96k)
	Dynamic range	89dB (DVD-Video 96k)
	DISC Format	DVD-Video / VIDEO-CD / CD-DA
	Quantifying bit number	16 / 20 / 24bit
	USB Standard	USB2.0 High Speed

Monitor Section	Picture size	6.75 inches(diagonal) wide
	W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
DVD Section	D/A Converter	24 / 32Bit
	Audio Decoder	Linear PCM
		Dolby Audio
		MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV
	Wow & Flutter	Below Measurable Limit
	Frequency response 96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	90.5dB (DVD-Video 96k)
	Dynamic range	89dB (DVD-Video 96k)
	DISC Format	DVD-Video / VIDEO-CD / CD-DA
	Quantifying bit number	16 / 20 / 24bit
	USB Standard	USB2.0 High Speed

Monitor Section	Picture size	6.75 inches(diagonal) wide
	W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
DVD Section	D/A Converter	24 / 32Bit
	Audio Decoder	Linear PCM
		Dolby Audio
		MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV
	Wow & Flutter	Below Measurable Limit
	Frequency response 96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	90.5dB (DVD-Video 96k)
	Dynamic range	89dB (DVD-Video 96k)
	DISC Format	DVD-Video / VIDEO-CD / CD-DA
	Quantifying bit number	16 / 20 / 24bit
	USB Standard	USB2.0 High Speed

K

J

Monitor Section	Picture size	6.75 inches(diagonal) wide
	W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
	Display system	TN LCD panel
	Drive system	TFT active matrix system
	Number of pixels	1,152,000
		800H x 480V x RGB
	Effective pixels	99.99%
	Pixel arrangement	RGB striped arrangement
	Back lighting	LED
DVD Section	D/A Converter	24 / 32Bit
	Audio Decoder	Linear PCM
		Dolby Audio
		MP3 / WMA / AAC / WAV / FLAC / Vorbis
	Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV
	Wow & Flutter	Below Measurable Limit
	Frequency response 96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
	Total harmonic distortion 1kHz	0.010%
	Signal to Noise ratio	90.5dB (DVD-Video 96k)
	Dynamic range	89dB (DVD-Video 96k)
	DISC Format	DVD-Video / VIDEO-CD / CD-DA
	Quantifying bit number	16 / 20 / 24bit
	USB Standard	USB2.0 High Speed