



A no-compromise loudspeaker and amplification solution for extreme home theater installations.







M3500IW



M3500IWNCE

ON-WALL OR IN-WALL

As the front, side and rear channels are all complimented by dedicated, extruded, aluminum enclosures, you can be confident the sound will remain consistent whether you choose the on-wall or in-wall installation option. The aesthetic choice is completely up to you. Display them proudly or hide them away. Our desire is to allow you the option of blending them seamlessly into your décor.





SPECIFICATIONS

MODEL	M3500OW	M3500IW	M3500IWNCE
PART	M3500OW	M3500IW	Surround Speaker Enclosure
Woofer	Dual 5" Coated Paper Cone	Dual 8" Coated Paper Cone	
Tweeter	1" Titanium Horn loaded	1" Titanium Horn loaded	
Frequency Response	70Hz – 20kHz	65Hz – 20kHz	
Power RMS	150 Watts	150 Watts	
Power Peak	300 Watts	300 Watts	
Impedance	4 ohm	4 ohm	
Dimensions	18 %" x 13" x 4 ¼" (480 x 330 x 108 mm)	18 %" x 13" x 3 ½" (480 x 330 x 102 mm)	18 1/8" x 13" x 3 1/2" (480 x 330 x 102 mm)
Cutout Dimensions		15 ½6" x 5 %6" (392 x 142 mm)	
Mounting Depth	5 ¼" (133 mm)	3 ½" (88 mm)	3 ½" (88 mm)



